Stats 1
Cust 1

STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S REPORT

OFFICE USE ONLY
Log No. 106528
Permit No. 064
Basin

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

455 NOTICE OF INTENT NO. 62004

1. OWNER David ITZA
MAILING ADDRESS P.O. Box 578 Battle MTN Nv 89820
ADDRESS AT WELL LOCATION ~~495~~ 26 Th. ST. Battle MTN 89820
Subdivision Name: Malone County: Lander

2. LOCATION SW ¼ NW ¼ Sec 24 T 32 N/S R 44 E
PERMIT/WAIVER No. 011-040-[redacted]
Issued by Water Resources Parcel No. 05
Latitude 40.630000 Longitude 116.974262
UTM E 50217 N 4497 ~~750~~ 474 ☒ NAD 27 ☐ NAD 83/WGS 84

3. WORKED PERFORMED
☒ New Well ☐ Replace ☐ Recondition ☐ Deepen ☐ Other

4. PROPOSED USE
☒ Domestic ☐ Irrigation ☐ Test ☐ Municipal/Industrial ☐ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☒ Rotary ☐ RVC ☐ Air ☐ Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Top Soil		0	5	5
Rocky Clay		5	20	15
Tan Clay		20	30	10
Blue Clay		30	80	50
Rocky Tan Clay		80	100	20
Gravel + Blue Clay		100	120	20
Tan Clay - Gravel		120	140	20

Date started: 5-19, 2008
Date completed: 5-20, 2008

9. WELL CONSTRUCTION
Depth Drilled 140 Feet Depth Cased 140 Feet

HOLE DIAMETER (BIT SIZE)

	From	To
10 5/8 Inches	0 Feet	140 Feet
Inches	Feet	Feet
Inches	Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
6 5/8		.188	T1	140

Perforations:
Type of perforation Sawed
Size of perforation 3/16 x 3
From 120 feet to 140 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Annular Seal: ☐ Yes ☐ No
☐ Neat Cement to ☐ Pumped ☐ Poured
☒ Cement Grout 5 to 55 ☐ Pumped ☒ Poured
☐ Concrete Grout to ☐ Pumped ☐ Poured
☐ ≥80% Bentonite Grout to ☐ Pumped ☐ Poured
Gravel Pack: ☐ Yes ☐ No 110 to 140 ☐ Pumped ☒ Poured
Type:
Bentonite Chips: ☒ Yes ☐ No 55 to 110 ☐ Pumped ☒ Poured
Type: 3/8"

7. Water Level
Static water level: 30 feet below land surface
Artesian Flow: G.P.M. P.S.I.
Water Temperature: Cold °F
Quality: Good

8. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☐ Air Lift

	G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
Rotary	60+	UNK	2 Hrs

STATE ENGINEERS OFFICE
2008 JUL -7 PM 2:05
RECEIVED

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name LBd Drilling Co. (Contractor)
Address P.O BOX 902 (Contractor)
Winca Nv 89446
Nevada contractor's license number issued by the State Contractor's Board 9605
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1807
Signed [signature] By driller performing actual drilling on site or contractor
Date

(Rev 06-08)

USE ADDITIONAL SHEETS IF NECESSARY