


STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S PLUGGING REPORT

OFFICE USE ONLY

Log No. 106568
Permit No. _____
Basin 568



PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

Please complete this form in its entirety in
accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 62758

1 OWNER Newmont Mining Corp.
MAILING ADDRESS PO Box 388
Valmy, NV 89435

ADDRESS AT WELL LOCATION Lone Tree Mine
Hole #SS-11
Subdivision Name: _____ County: Humboldt

2 LOCATION SW $\frac{1}{4}$ ~~SE~~ $\frac{1}{4}$ Sec 11 T 34N N/S R 42 E
PERMIT/WAIVER No. NE M/D-975
Issued by Water Resources Parcel No. _____

Latitude 40.93846 UTM E 481992 NAD 27
Longitude 117.21397 N 4520678 NAD 83/WGS 84

3 TYPE OF WELL
 Domestic Irrigation Test
 Municipal/Industrial Monitor Stock

Is this well being plugged because a replacement well was drilled? No
If yes, what is replacement well NOI? _____

Is there an existing well log? Yes
If yes, what is NDWR well log #? 67376

4 EXISTING WELL CONSTRUCTION
Depth Drilled 496 Feet Depth Cased 496 Feet

7 WELL PLUGGING PROCEDURE
Was well cleaned out to total depth? yes no
If well was not cleaned out to total depth, please explain why: _____

EXISTING CASING SCHEDULE				
Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
8 5/8	32	.30	+3	3
4 1/2	Sch 80	PVC Blank	+2	60
4 1/2	Sch 80	PVC Screen	60	496

Was the well contaminated? yes no
Was the casing pulled? yes no
Was the casing over drilled? yes no
If casing was left in place, please show where additional perforations were made:
Additional Perforations:
Type of perforator used: _____

Existing Perforations:

Type of perforation	Slot Size of perforation	From	feet to	feet
	0.02	60	feet to	496 feet
			feet to	feet
			feet to	feet
			feet to	feet
			feet to	feet

Additional Perforations:

From	feet to	feet	Number of perfs per linear foot

5 WATER LEVEL
Static water level 260 feet below land surface
Artesian flow No G.P.M. N/A P.S.I.
Water temperature Cool ° F Quality Good

8 WELL PLUGGING MATERIALS

From	feet to	feet	Material Used	<input type="checkbox"/> Pumped	<input type="checkbox"/> Poured
496	feet to	20	Super Plug	<input checked="" type="checkbox"/>	<input type="checkbox"/>
20	feet to	0	Cement	<input checked="" type="checkbox"/>	<input type="checkbox"/>
	feet to			<input type="checkbox"/>	<input type="checkbox"/>
	feet to			<input type="checkbox"/>	<input type="checkbox"/>
	feet to			<input type="checkbox"/>	<input type="checkbox"/>
	feet to			<input type="checkbox"/>	<input type="checkbox"/>

6 Additional Notes or Comments
Pumped super plug through trimmie from bottom of hole to surface. Cement plug from 20' to surface.
36 - 50lb Bags Super Plug
3 - Cement

Neat Cement Fluid Weight 15.4 lbs/gal
Bentonite Grout _____ % bentonite
Date Started 6/12/2008
Date Completed 6/12/2008

STATE ENGINEERS OFFICE
2008 JUN 25 AM 11:49
RECEIVED

9 DRILLER'S CERTIFICATION
This well was plugged and abandoned under my supervision and the report is true to the best of my knowledge.
Name Eklund Drilling Company, Inc. Contractor
Address PO Box 2748 Contractor
Elko, NV 89803
Nevada contractor's license number issued by the State Contractor's Board 0030823
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1777
Signed Dennis L. White By driller performing actual drilling on site or contractor
Date 6/12/2008

USE ADDITIONAL SHEETS IF NECESSARY

(Rev. 05-06)