


STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S PLUGGING REPORT

OFFICE USE ONLY 100570

Log No. _____
Permit No. _____
Basin 765



PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

Please complete this form in its entirety in
accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 61367

1 OWNER Newmont Mining Corp
MAILING ADDRESS Po Box 388
Valmy, NV 89435

ADDRESS AT WELL LOCATION Lone Tree Mine
Hole #SS-16
Subdivision Name: _____ County: Humboldt

2 LOCATION NW 1/4 NE 1/4 Sec 11 T 34N N/S R 42 E
PERMIT/WAIVER No. 110-975
Issued by Water Resources Parcel No. _____

Latitude 40.842878 UTM E 482259 NAD 27
Longitude 117.210443 N 4521125 NAD 83/WGS 84

3 TYPE OF WELL
 Domestic Irrigation Test
 Municipal/Industrial Monitor Stock

Is this well being plugged because a replacement well was drilled? No
If yes, what is replacement well NOI? _____

Is there an existing well log? Yes
If yes, what is NDWR well log #? 67323

4 EXISTING WELL CONSTRUCTION
Depth Drilled 439 Feet Depth Cased 439 Feet

7 WELL PLUGGING PROCEDURE
Was well cleaned out to total depth? yes no
If well was not cleaned out to total depth, please explain why: _____

EXISTING CASING SCHEDULE				
Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
8 5/8	32	.30	+3	3
4 1/2	Sch 80	PVC	+2	60

Was the well contaminated? yes no
Was the casing pulled? yes no
Was the casing over drilled? yes no

Existing Perforations:

Type of perforation	Size of perforation	From	feet to	feet
4 1/2" sch 80 PVC Screen	0.02	60	feet to	439 feet
			feet to	

Additional Perforations:

Type of perforator used: _____

From	feet to	feet	Number of perfs per linear foot

5 WATER LEVEL
Static water level Dry feet below land surface
Artesian flow _____ G.P.M. _____ P.S.I.
Water temperature _____ ° F Quality _____

8 WELL PLUGGING MATERIALS

Material Used

From	feet to	feet	Material	<input type="checkbox"/> Pumped	<input type="checkbox"/> Poured
439	feet to	25 feet	Bentonite Grout	<input checked="" type="checkbox"/>	<input type="checkbox"/>
25	feet to	23 feet	Chip	<input type="checkbox"/>	<input checked="" type="checkbox"/>
23	feet to	0 feet	Neat Cement	<input type="checkbox"/>	<input checked="" type="checkbox"/>
	feet to			<input type="checkbox"/>	<input type="checkbox"/>
	feet to			<input type="checkbox"/>	<input type="checkbox"/>
	feet to			<input type="checkbox"/>	<input type="checkbox"/>

6 Additional Notes or Comments
No Static water, well was dry. No additional perforations made knocked bottom cap off with trimmie pipe.

Neat Cement Fluid Weight 15.3 lbs/gal
Bentonite Grout 12.5 % bentonite
Date Started 6/4/2008
Date Completed 6/4/2008

STATE ENGINEERS OFFICE
2008 JUN 25 AM 11:49

9 DRILLER'S CERTIFICATION
This well was plugged and abandoned under my supervision and the report is true to the best of my knowledge.
Name Eklund Drilling Company, Inc. Contractor
Address PO Box 2748 Contractor
Elko, NV 89803
Nevada contractor's license number issued by the State Contractor's Board 0030823
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 2347
Signed Alve Schaeber By (signature)
Date 6/9/2008
By driller performing actual drilling on site or contractor