

STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S PLUGGING REPORT

OFFICE USE ONLY **106643**
Log No. _____
Permit No. _____
Basin **665**

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

Please complete this form in its entirety in
accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 61403

1 OWNER Newmont Mining Corp.
MAILING ADDRESS PO Box 388
Valmy, NV 89435

ADDRESS AT WELL LOCATION Lone Tree Mine
Hole #WW-21
Subdivision Name: _____ County: Humboldt

2 LOCATION SW 1/4 SW 1/4 Sec 12 T 34N N/S R 42 E
PERMIT/WAIVER No. 59249/59250
Issued by Water Resources Parcel No.

Latitude 40.879829 UTM E 482861 NAD 27
Longitude 112.263262 N 4519675 NAD 83/WGS 84

3 TYPE OF WELL
 Domestic Irrigation Test
 Municipal/Industrial Monitor Stock

Is this well being plugged because a replacement well was drilled? No
If yes, what is replacement well NOI? _____

Is there an existing well log? Yes
If yes, what is NDWR well log #? 67336

4 EXISTING WELL CONSTRUCTION
Depth Drilled 1510 Feet Depth Cased 1498 Feet

EXISTING CASING SCHEDULE				
Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
50	362.3	.688	0	41
40	171.68	.406	0	60
34	134.68	.375	0	140
24			0	1498

Existing Perforations:

Type of perforation	Size of perforation	Depth	Notes
Louvered	0.125		
From	346	feet to 366	feet
From	649	feet to 1498	feet
From		feet to	feet
From		feet to	feet
From		feet to	feet

5 WATER LEVEL
Static water level 526 feet below land surface
Artesian flow No G.P.M. N/A P.S.I.
Water temperature Warm °F Quality Good

6 Additional Notes or Comments
Take static measurement. Go to bottom of well and make sure it is clean. Trip back to 150' below static (680') and take H2O sample. Trip out and put on perforator. Perforate well 140-340 & 370-640. Take 24" perforator off. Trip open-ended pipe in to 1400' and start pumping bentonite grout slurry. Pump in over 150% of hole volume 80,500 gal. Pour in slowly 3/4" hole plug, 52 Super sacks. Bring up to 22' of surface. Pour in cement slurry, approx. 564 gal. Bring up to surface.

60 sacks - 564 gal slurry
1750 Sacks 80,500 gallons

7 WELL PLUGGING PROCEDURE
Was well cleaned out to total depth? yes no
If well was not cleaned out to total depth, please explain why: _____

Was the well contaminated? yes no
Was the casing pulled? yes no
Was the casing over drilled? yes no

If casing was left in place, please show where additional perforations were made:
Additional Perforations:

Type of perforator used:	From	To	Number of perfs per linear foot
Star 12 Row	140	340	5
	370	640	5

8 WELL PLUGGING MATERIALS

From	To	Material Used	Notes
1498	487	Super Plug	<input checked="" type="checkbox"/> Pumped <input type="checkbox"/> Poured
487	22	3/4" Hole Plug	<input type="checkbox"/> Pumped <input checked="" type="checkbox"/> Poured
22	0	Cement	<input type="checkbox"/> Pumped <input checked="" type="checkbox"/> Poured
			<input type="checkbox"/> Pumped <input type="checkbox"/> Poured
			<input type="checkbox"/> Pumped <input type="checkbox"/> Poured
			<input type="checkbox"/> Pumped <input type="checkbox"/> Poured

Neat Cement Fluid Weight 15 lbs/gal
Bentonite Grout 12.5 % bentonite
Date Started 8/20/2008
Date Completed 8/25/2008

9 DRILLER'S CERTIFICATION
This well was plugged and abandoned under my supervision and the report is true to the best of my knowledge.
Name Eklund Drilling Company, Inc. Contractor
Address PO Box 2748 Contractor
Elko, NV 89803
Nevada contractor's license number issued by the State Contractor's Board 0030823
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 2089
Signed Donald School By driller performing actual drilling on site or contractor
Date 8/25/2008

2008 SEP 11 PM 1:22
STATISTICAL DIVISION