

**STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S PLUGGING REPORT**

OFFICE USE ONLY
 Log No. 101047
 Permit No. _____
 Basin 149

**PRINT OR TYPE ONLY
DO NOT WRITE ON BACK**

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 61620

1. OWNER Stone Cabin ADDRESS AT WELL LOCATION Stone Cabin
 MAILING ADDRESS 3856 SW Sam Snead Court
Redmond, OR 97756

2. LOCATION SW ¼ NE ¼ Sec 14 T 01N N/S R 46 E Latitude 37.93747 UTM E NAD 27
 PERMIT/WAIVER No. 65021 Longitude 116.79131 N NAD 83
65021, Issued by Water Resources Parcel No. _____ Subdivision Name: _____ County: Nye

3. TYPE OF WELL
 Domestic Irrigation Test
 Municipal/Industrial Monitor Stock
 Is this well being plugged because a replacement well was drilled? Yes No
 If yes, what is replacement well NOI? See Attached Is there an existing well log? Yes
 If yes, what is NDWR well log #? 101047

4. EXISTING WELL CONSTRUCTION

Depth Drilled 450 Feet Depth Cased 450 Feet

EXISTING CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)

6. WELL ABANDONMENT PROCEDURE

Was well cleaned out to total depth? yes no
 If well was not cleaned out to total depth, please explain why: _____

Was the well contaminated? yes no
 Was the casing pulled? yes no
 Was the casing over drilled? yes no

Existing Perforations:

Type of perforation	Size of perforation	From	feet to	feet

If casing was left in place, please show where additional perforations were made:

Additional Perforations:

Type of perforator used:	Hot Air
From <u>50</u> feet to <u>200</u> feet	Number of perfs per linear foot <u>40</u>

5. WATER LEVEL

Static water level 125 feet below land surface
 Artesian flow _____ G.P.M. _____ P.S.I.
 Water temperature _____ °F Quality _____

7. WELL ABANDONMENT MATERIALS

From	feet to	Material Used	Pumped	Poured
From <u>20</u> feet to <u>450</u> feet		Gopher Grout	<input checked="" type="checkbox"/>	<input type="checkbox"/>
From <u>0</u> feet to <u>20</u> feet		Cement	<input type="checkbox"/>	<input checked="" type="checkbox"/>
			<input type="checkbox"/>	<input type="checkbox"/>
			<input type="checkbox"/>	<input type="checkbox"/>
			<input type="checkbox"/>	<input type="checkbox"/>
			<input type="checkbox"/>	<input type="checkbox"/>

Additional Notes or Comments

The well was perforated from 50 feet to 200 feet. Ran tremmie pipe and pumped Gopher Grout to 20 feet and set neat cement to surface.

Neat Cement Fluid Weight _____ lbs/gal
 Bentonite Grout _____ 20% Solids _____ % bentonite
 Date Started 8/2/2008
 Date Completed 8/3/2008

2008 SEP 11 PM 12:54
 STATE OF NEVADA
 DIVISION OF WATER RESOURCES
65021
116.79041 NAD27

8. DRILLER'S CERTIFICATION

This well was plugged and abandoned under my supervision and the report is true to the best of my knowledge.

Name Hydro Resources Nevada, Inc., dba Humboldt Drilling & Pump Co., Inc.
 Contractor

Address 4975 W. Winnemucca Blvd.
 Contractor

Winnemucca, NV 89445
 Nevada contractor's license number 56797
 issued by the State Contractor's Board
 Nevada driller's license number issued by the 1713 Ray Wilson
 Division of Water Resources, the on-site driller

Signed George James OFFICE
 By driller performing actual drilling on site or contractor

Date 8/27/2008