

**STATE OF NEVADA**  
**DIVISION OF WATER RESOURCES**  
**WELL DRILLER'S REPORT**

OFFICE USE ONLY  
 Log No. 106694  
 Permit No. \_\_\_\_\_  
 Basin Ø71

PRINT OR TYPE ONLY

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. **62658**

1. OWNER **Steve Nichols** ADDRESS AT WELL LOCATION **3100 East Donald Lane Winnemucca, NV 89445**  
 MAILING ADDRESS **PO Box 2504 Winnemucca, NV 89446** **Winnemucca, NV 89445**  
 LOCATION NE SE SW 1/4 SW 1/4 Sec 25 T35N R37E **Subdivision Name:** \_\_\_\_\_ **County: Humboldt**  
 PERMIT/WAIVER NO. **014-153-02** Latitude **N40°87908** UTM E \_\_\_\_\_  NAD 27  
 Issued by Water Resources Parcel. No. \_\_\_\_\_ Longitude **W117°75936** N \_\_\_\_\_  NAD 83/WGS 84

3. WORK PERFORMED  New Well  Replace  Recondition  Deepen  Other \_\_\_\_\_  
 4. PROPOSED USE  Domestic  Irrigation  Test  Municipal/Industrial  Monitor  Stock  
 5. WELL TYPE  Cable  Rotary  RVC  Air  Other \_\_\_\_\_

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thick-ness
Sand & Gravel	X	130	150	20
Clay		150	160	10
Course Sand & Gravel		160	190	30
Fine sand/gravel cobbles		190	200	10
Clay		200	210	10
Course gravel	X	210	230	20
Sand/gravel w/clay		230	285	55

2008 AUG 11 PM 12:22  
 STATE ENGINEERS OFFICE

Deepening of log # 83331  
 N 40.879176  
 W 117.758397 NAD 83

9. WELL CONSTRUCTION  
 Depth Drilled **285** Feet Depth Cased **285** Feet  
 HOLE DIAMETER (BIT SIZE)  
 From **6 1/4"** Inches To **130** Feet **285** Feet  
 \_\_\_\_\_ Inches \_\_\_\_\_ Feet \_\_\_\_\_ Feet  
 \_\_\_\_\_ Inches \_\_\_\_\_ Feet \_\_\_\_\_ Feet  
 CASING SCHEDULE  

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
<b>5"</b>	<b>8</b>	<b>188</b>	<b>125</b>	<b>285</b>

Perforations:  
 Type of perforation **Factory Cut**  
 Size of perforation **3/32 x 4**  
 From **225** feet to **285** feet  
 From \_\_\_\_\_ feet to \_\_\_\_\_ feet

Annular Seal:  Yes  No  
 Existi  
 Neat Cement \_\_\_\_\_ to \_\_\_\_\_  Pumped  Poured  
 Cement Grout \_\_\_\_\_ to \_\_\_\_\_  Pumped  Poured  
 Concrete Grout \_\_\_\_\_ to \_\_\_\_\_  Pumped  Poured  
 ≥30% Bentonite Grout \_\_\_\_\_ to \_\_\_\_\_  Pumped  Poured  
 Gravel Pack:  Yes  No **Natur** al to \_\_\_\_\_  Pumped  Poured  
 Type: \_\_\_\_\_  
 Bentonite Chips:  Yes  No \_\_\_\_\_ to \_\_\_\_\_  Pumped  Poured  
 Type: \_\_\_\_\_

7. Water Level  
 Static water level: **127'** feet below land surface  
 Artesian Flow: **N/A** G.P.M. **N/A** P.S.I  
 Water Temperature: **Cool** °F  
 Quality: **Good**

8. WELL TEST DATA

TEST METHOD:	G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
<input type="checkbox"/> Bailer <input type="checkbox"/> Pump <input checked="" type="checkbox"/> Air Lift	<b>20</b>		<b>3.0</b>

10. DRILLER'S CERTIFICATION  
 This well was drilled under my supervision and the report is true to the best of my knowledge.  
 Name **Fred Anderson Drilling, Inc.**  
 (CONTRACTOR)  
 Address **10760 S. Grass Valley Road**  
 (CONTRACTOR)  
**Winnemucca, NV 89445**  
 Nevada contractor's license number issued by the State Contractor's Board **021467**  
 Nevada driller's license number issued by the Division of Water Resources, the on-site driller **2083**  
 Signed **Fred Anderson Drilling Inc**