STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S REPORT

OFFICE USE ONLY
Log No. 706716
Permit No.
Basin 070

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 31574

1. OWNER Flying J Inc.
MAILING ADDRESS 333 W. Center Street
N. Salt Lake Utah 84054

ADDRESS AT WELL LOCATION 1880 W. Winnemucca Blvd
Winnemucca, Nevada
Subdivision Name: County: Humboldt

2. LOCATION SE ¼ SW ¼ Sec 30 T 36 N/S R 38 E
PERMIT/WAIVER No. 015-292-06
Issued by Water Resources Parcel No.

Latitude N40° 57' 36.27" UTM E
Longitude W117° 44' 50.52" N
☒ NAD 83/WGS 84
Facility # E-000971 MW-15

3. WORKED PERFORMED
☒ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Other

4. PROPOSED USE
☐ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☒ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☐ Rotary ☐ RVC
☐ Air ☒ Other Auger

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Aphaltic Concrete		0	½	½
Sand w/silt, gravel		½	15½	15
	Wet	15½	25	9½

N40.960187
W 117.746398 NAD27

RECEIVED 2008 AUG -4 AM 11:27 STATE ENGINEER'S OFFICE

Date started: 7-8-24, 20 08
Date completed: 7-8-24, 20 08

7. Water Level
Static water level: 15.5 feet below land surface
Artesian Flow: G.P.M. P.S.I.
Water Temperature: °F
Quality:

8. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☐ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
NA		

9. WELL CONSTRUCTION
Depth Drilled 25 Feet Depth Cased 25 Feet

HOLE DIAMETER (BIT SIZE)

	From	To
8 Inches	0 Feet	25 Feet
Inches	Feet	Feet
Inches	Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
2"	sch 40	ASTM F 480	0	25

Perforations:
Type of perforation Factory Slots
Size of perforation .020
From 5 feet to 25 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Annular Seal: ☒ Yes ☐ No
☐ Neat Cement to ☐ Pumped ☐ Poured
☐ Cement Grout to ☐ Pumped ☐ Poured
☒ Concrete Grout 0 to 3 ☐ Pumped ☒ Poured
☐ ≥30% Bentonite Grout to ☐ Pumped ☐ Poured

Gravel Pack: ☒ Yes ☐ No 4 to 25 ☐ Pumped ☒ Poured
Type: #3 Monterey Sand
Bentonite Chips: ☒ Yes ☐ No 3 to 4 ☐ Pumped ☒ Poured
Type: 3/8 Bentonite Hole Plug

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name (Contractor) Elite Drilling Inc.
Address (Contractor) 4255 W. Post Rd.
Las Vegas, Nevada 89118
Nevada contractor's license number issued by the State Contractor's Board 054931
Nevada driller's license number issued by the Division of Water Resources, the on-site driller M-1944
Signed Thomas M. Beall
(By driller performing actual drilling on-site or contractor)
Date 7-30-08

(Rev. 05-06)

USE ADDITIONAL SHEETS IF NECESSARY

(NSPO 3-08) (O) 627