

**STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S PLUGGING REPORT**

OFFICE USE ONLY

Log No. 106892
Permit No. _____
Basin 153

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

Please fill in this form in its entirety in
accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 62303

1. OWNER Diamond Valley Ranch
MAILING ADDRESS P.o. Box 920 Lake Oswego, OR 970
Lake Oswego, OR 97034

ADDRESS AT WELL LOCATION #6 Diamond Valley Ranch
Eureka, NV 89316

2. LOCATION SW 1/4 NE 1/4 Sec 27 T 21 R 53
PERMIT NO 21930 Parcel No.

Latitude 39.66174 Longitude -115.9892 WGS 84
Subdivision Name _____ County Eureka

3. TYPE OF WELL
Irrigation

Is this well being plugged because a replacement well was drilled? No
If yes what is replacement well NOI?

Is there an existing well log? Yes
If yes, what is NDWR well log #? ~~708~~ 86190

4. EXISTING WELL CONSTRUCTION
Depth Drilled 355 Feet Depth Cased ~~355~~ ³⁵⁵ Feet

7. WELL PLUGGING PROCEDURE
Was well cleaned out to total depth? Yes
If well was not cleaned out to total depth, please explain why:

EXISTING CASING SCHEDULE

Size O.D. (inches)	Weight/Ft. (Pounds)	Wall Thickness	From (Feet)	To (Feet)
16	42.09	0.25	0	248
14	36.7	0.25	355	188

Was well contaminated? No
Was casing pulled? No
Was casing overdrilled? No

If casing was left in place, please show where additional perforations were made:

Additional Perforations:

Type perforator used: Mills Knife
From 0 To 188 Number of perfs per linear foot 12

Existing Perforations:

Type perforation Mill Cut
Size perforation 0.032
From 355 feet to 188 feet
From 125 feet to 105 feet

5. WATER LEVEL

Static Water Level 134 feet below land surface
Artesian Flow G.P.M. P.S.I.
Water temperature ° F Quality unknown

8. WELL PLUGGING MATERIALS

From	To	Material	
355 Feet to	50 Feet	Bentonite	Pumped
50 Feet to	0 Feet	Neat Cement	Pumped

6. Additional Notes or Comments

Perforated well from 188' to 0'. Installed 105 Bags of 20% bentonite from 355' to 50'. From 50' to surface Neat cement was used.

Neat Cement Fluid Weight 156 lbs/gal
Bentonite Grout 20 % Bentonite
Date Started 3/28/2008
Date Completed 5/2/2008

N 37.661656
W 115.987405 NAD87

9. DRILLER'S CERTIFICATION

This well was drilled under my supervision and the report is true to the best of my knowledge.

Name Parsons Drilling, Inc.
Contracto
Address 403 McLean Road
Fallon, NV 89407

Contracto
Nevada contractor's license number 29064
issued by the State Contractor's Board
Nevada driller's license number issued by the 1753
Division of Water Resource, the on-site driller

Signed W. Ryan Parsons
By driller performing the actual drilling on site for contract
Date 7/28/2008

RECORDED
2008 AUG 22 AM 11:45
STATE ENGINEERING OFFICE