STATE OF NEVADA

DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

OFFICE USE ONLY
Log No. 106967
Permit No.
Basin 073A

PRINT OR TYPE ONLY

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 62661

1. OWNER Mike & Cathy Pinto
MAILING ADDRESS PO Box 117, Wadsworth, NV 89442

ADDRESS AT WELL LOCATION 12600 Reno Drive
Lovelock, Nv
Subdivision Name: Humboldt River Ranch *County:* Pershing

2. LOCATION SE ¼ NW ¼ Sec15T30N/ R33E
PERMIT/WAIVER NO. 010-115-01
Issued by Water Resources Parcel. No.

Latitude N40°46550 UTM E ☐ NAD 27
Longitude W118°26007 N ☒ NAD 83/WGS 84

3. WORK PERFORMED
☒ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Other

4. PROPOSED USE
☒ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☐ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☒ Rotary ☐ RVC
☐ Air ☐ Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Cobles & Gravel		0	70	70
Course gravel		70	85	15
Coble & gravel		85	105	20
Cement/rock		105	160	55
Coble/gravel		160	230	70
cement/rock		230	258	28
cobles/gravel/clay		258	280	22
rock		280	295	15
cobles		295	305	10
sand & gravel	X	305	315	10
rock		315	319	4
fractured rock		319	321	3
sand/gravel w/clay	X	321	345	24
rock		345	359	14

N 40.465593
W 118.259091 NAD27

Date started: August 14, 20 08
Date completed: August 18, 20 08

7. *Water Level*
Static water level: 263 feet below land surface
Artesian Flow: N/A G.P.M. N/A P.S.I
Water Temperature: Cool °F
Quality: Good

8. WELL TEST DATA
TEST METHOD: ☐ Bailer ☒ Pump ☐ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
15		10

9. *WELL CONSTRUCTION*
Depth Drilled 359 Feet Depth Cased 359 Feet

HOLE DIAMETER (BIT SIZE)

	From	To
10 5/8 Inches	0 Feet	359 Feet
Inches	Feet	Feet
Inches	Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
6 5/8	10	188	+1	20
6.625	4.06	.316	20	259

Perforations:
Type of perforation Factory Cut Slots
Size of perforation 050
From 299 feet to 359 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Annular Seal: ☒ Yes ☐ No
☒ Neat Cement 0 to 50 ☒ Pumped ☐ Poured
☐ Cement Grout to ☐ Pumped ☐ Poured
☐ Concrete Grout to ☐ Pumped ☐ Poured
☐ ≥30% Bentonite Grout to ☐ Pumped ☐ Poured
Gravel Pack: ☒ Yes ☐ No 50 to 359 ☐ Pumped ☒ Poured
Type:
Bentonite Chips: ☐ Yes ☒ No to ☐ Pumped ☐ Poured
Type:

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name Fred Anderson Drilling, Inc. (CONTRACTOR)
Address 10760 S. Grass Valley Road (CONTRACTOR)
Winnemucca, NV 89445
Nevada contractor's license number issued by the *State Contractor's Board* 021467
Nevada driller's license number issued by the Division of Water Resources, the *on-site driller* 2083
Signed Fred Anderson Drilling Inc
By driller performing actual drilling on site or contractor
Date September 1, 2008

(Rev 05-06) USE ADDITIONAL SHEETS IF NECESSARY

Forms Provided by Forms-On-A-Disk · (214) 340-9429 · FormsOnADisk.com