

STATE OF NEVADA  
 DIVISION OF WATER RESOURCES  
**WELL DRILLER'S PLUGGING REPORT**

OFFICE USE ONLY

Log No. 106974  
 Permit No. \_\_\_\_\_  
 Basin 153

PRINT OR TYPE ONLY  
 DO NOT WRITE ON BACK

*Corrected*  
 Please fill in this form in its entirety in  
 accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 59208

1. OWNER Diamond Valley Ranch  
 MAILING ADDRESS P.o. Box 920 Lake Oswego, OR 970  
 Lake Oswego, OR 97034

ADDRESS AT WELL LOCATION Diamond Valley #2  
 Eureka, NV 89316

2. LOCATION SW 1/4 ~~1/4~~ 1/4 Sec 28 T 21 R 53  
 PERMIT NO. ~~10338~~ 21929 Parcel No.

Latitude 39.66160 Longitude -116.01635  WGS 84  
 Subdivision Name \_\_\_\_\_ County Eureka

3. TYPE OF WELL  
 Irrigation

Is this well being plugged because a  
 replacement well was drilled?  
 If yes what is replacement well NO?

Yes

Is there an existing well log?

~~Yes~~ NO

If yes, what is NDWR well log #? ~~7052~~

4. EXISTING WELL CONSTRUCTION  
 Depth Drilled 186 Feet Depth Cased 186 Feet

EXISTING CASING SCHEDULE

Size O.D. (inches)	Weight/Ft. (Pounds)	Wall Thickness	From (Feet)	To (Feet)
16	42.0	0.250	0	186

Existing Perforations:

Type perforation Johnson Free-Flo  
 Size perforation 0.250  
 From 126 feet to 186 feet

7. WELL PLUGGING PROCEDURE

Was well cleaned out to total depth? Yes

If well was not cleaned out to total depth, please explain why:

Was well contaminated? No

Was casing pulled? No

Was casing overdrilled? No

If casing was left in place, please show where additional perforations were made:

Additional Perforations:

Type perforator used: Air Roller  
 From 0 To 125 Number of perfs per linear foot 16

5. WATER LEVEL

Static Water Level 160 feet below land surface  
 Artesian Flow G.P.M. P.S.I.  
 Water temperature ° F Quality

8. WELL PLUGGING MATERIALS

From	To	Material	
0 Feet to	50 Feet	Neat Cement	Pumped
50 Feet to	186 Feet	Bentonite	Pumped

6. Additional Notes or Comments

Pumped in 72 bags of 20% Bentonite grout from bottom to 50 ft.  
 Installed 3 yds of neat cement from 50 ft. to surface.

Neat Cement Fluid Weight 156 lbs/gal

Bentonite Grout 20 % Bentonite

Date Started 3/16/2007

Date Completed 11/6/2007

9. DRILLER'S CERTIFICATION

This well was drilled under my supervision and the report is true to the best of my knowledge.

Name Parsons Drilling, Inc.

Contracto

Address 403 McLean Road

Fallon, NV 89407

Contracto

Nevada contractor's license number 29064  
 issued by the State Contractor's Board

Nevada driller's license number issued by the 1753  
 Division of Water Resource, the on-site driller

Signed *Wayne P... [Signature]*

By driller performing the actual drilling on site or contract

Date 12/5/2007

RECEIVED  
 2008 JUN 30 PM 12:17  
 STATE ENGINEERS OFFICE

Returned 6/27/2008

N 39.661623  
 W 116.015266 NAD27

RECEIVED  
 MAY 22 2008  
 BY: \_\_\_\_\_