WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S REPORT
Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 107076
Permit No.
Basin 184

NOTICE OF INTENT NO. 61752

1. OWNER Richard Fillman
MAILING ADDRESS 23217 So. 182nd Street
Gilbert, Az 85297

ADDRESS AT WELL LOCATION Sacramento Pass

2. LOCATION SE ¼ NW ¼ Sec. 21 T 15 N/S R 68 E White Pine County
PERMIT NO. (Issued by Water Resources) APN 012-070-09 (Parcel No.) (Subdivision Name)

3. WORK PERFORMED
[X] New Well [ ] Replace [ ] Recondition
[ ] Deepen [ ] Abandon [ ] Other

4. PROPOSED USE
[X] Domestic [ ] Irrigation [ ] Test
[ ] Municipal/Industrial [ ] Monitor [ ] Stock

5. WELL TYPE
[ ] Cable [X] Rotary [ ] RVC
[X] Air [ ] Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Rocks & Boulders		0	5	5
Hard Pan		5	15	10
Cemented Rock & Bldrs		15	60	45
Limestone		60	85	25
Altered Limestone		85	95	10
Altered Limestone w/	X	95		
Clay Stringers			120	25
Limestone		120	150	30
Altered Limestone		150	240	90
Altered Limestone w/	X	240		
Clay Stringers			255	15
Clay		255	260	5
Limestone		260	300	40
Fractured Limestone	X	300	320	20
N 39.152116				
W 114.347125 NAD27				
WGS 84				
Lat. N39°09' 07.4"				
Long. W 114°20' 52.7"				
Elevation 6,982'				

Date started August 13, 2008
Date complated August 28, 2008

7. WELL TEST DATA
TEST METHOD: [ ] Bailer [ ] Pump [ ] Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
20	229	1 1/2

8. WELL CONSTRUCTION
Depth Drilled 320 Feet Depth Cased 320 Feet

HOLE DIAMETER (BIT SIZE)

		From	To
10-5/8 Inches		0 Feet	320 Feet
Inches		Feet	Feet
Inches		Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
6-5/8	12.92	.188	0	320

Perforations:
Type perforation Factory
Size perforation 1/8" x 2 1/3" 6 Rows
From 100 feet to 140 feet
From 160 feet to 200 feet
From 220 feet to 240 feet
From 280 feet to 320 feet
From feet to feet

Surface Seal: [X] Yes [ ] No
Depth of Seal 50
Placement Method: [ ] Pumped [X] Poured
Seal Type: [ ] Neat Cement [X] Cement Grout [ ] Concrete Grout

Gravel Packed: [X] Yes [ ] No
From 50 feet to 320 feet

9. WATER LEVEL
Static water level 86 feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature Cold °F Quality Good

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name Christiansen Drilling, Inc. (Contractor)
Address 557 Ely Avenue (Contractor)
Ely, Nv 89301
Nevada contractor's license number issued by the State Contractor's Board 14790
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1793
Signed Rick Lewis By Jerald D. Christiansen (By driller performing actual drilling on site or contractor)
Date September 26, 2008

(Rev. 12-01) USE ADDITIONAL SHEETS IF NECESSARY (O)-627