STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S REPORT

OFFICE USE ONLY
Log No. 107210
Permit No.
Basin 212

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 34954

1. OWNER County of Clark
MAILING ADDRESS 5005 Grand Central
LV, Nv.

ADDRESS AT WELL LOCATION Public right of way
LV, NV
Subdivision Name: County: Clark

2. LOCATION NE ¼ SE ¼ Sec 09 T 21 N/S R 61 E
PERMIT/WAIVER No. NDEP 070621-02 (Issued by Water Resources) APN 162-09-799-005 (Parcel No.)

Latitude 36.134.03 °N
Longitude - 115.159.36 °W
UTM E
N
☐ NAD 27
☒ NAD 83/WGS 84

3. WORKED PERFORMED
☒ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Other

4. PROPOSED USE
☐ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☒ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☐ Rotary ☐ RVC
☐ Air ☒ Other HSA

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
asphalt		0	0.25	.25
aggregate base		0.25	1.5	1.25
silty sand		1.5	3	1.5
clayey sand		3	5	2
sandy clay		5	7.5	2.5
clayey gravel		7.5	9.5	2
cemented sand & gravel		9.5	11	1.5
silty sand		11	17	6
sandy clay		17	26	9
cemented sand & gravel		26	34	8
MW-11				

Date started: 9-5, 20 08
Date completed: 9-5, 20 08

9. WELL CONSTRUCTION
Depth Drilled 34 Feet Depth Cased 34 Feet

HOLE DIAMETER (BIT SIZE)

		From	To
8 Inches		0 Feet	34 Feet
Inches		Feet	Feet
Inches		Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
2		sch 40 PVC	0	34

Perforations:
Type of perforation machine slotted
Size of perforation .020
From 19 feet to 34 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Annular Seal: ☐ Yes ☐ No
☐ Neat Cement to ☐ Pumped ☐ Poured
☐ Cement Grout to ☐ Pumped ☐ Poured
☒ Concrete Grout 0 to 4 ☐ Pumped ☒ Poured
☐ ≥30% Bentonite Grout to ☐ Pumped ☐ Poured

Gravel Pack: ☒ Yes ☐ No 17 to 34 ☐ Pumped ☒ Poured
Type: Silica Sand #12
Bentonite Chips: ☒ Yes ☐ No 4 to 17 ☐ Pumped ☒ Poured
Type: 3/8" chips

7. Water Level
Static water level: 29.08 feet below land surface
Artesian Flow: G.P.M. P.S.I.
Water Temperature: °F
Quality:

8. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☐ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)

DCNR/DWR RECEIVED
OCT 14 2008
LAS VEGAS OFFICE

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name Terracon (Contractor)
Address 750 Pilot Rd, Ste F (Contractor)
Las Vegas NV 89119
Nevada contractor's license number issued by the *State Contractor's Board*
Nevada driller's license number issued by the Division of Water Resources, the *on-site driller* 2077
Signed (By driller performing actual drilling on site or contractor)
Date

(Rev. 05-06)

USE ADDITIONAL SHEETS IF NECESSARY