

**STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S PLUGGING REPORT**

OFFICE USE ONLY 107440

Log No. _____
 Permit No. _____
 Basin 069
 NOTICE OF INTENT NO. 61568

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

Please complete this form in its entirety in
accordance with NRS 534.170 and NAC 534.340

1 OWNER Winnemucca Farms ADDRESS AT WELL LOCATION Well #111
 MAILING ADDRESS One Potato Place Golconda Butte
Winnemucca, Nevada 89445 Subdivision Name: _____ County: Humboldt
 2 LOCATION SW ¼ NW ¼ Sec 23 T 37N N/S R 39 E Latitude 41.06930 UTM E _____ NAD 27
 PERMIT/WAIVER No. 65847 Longitude 117.56334 N _____ NAD 83/WGS 84
Issued by Water Resources Parcel No.

3 TYPE OF WELL Is this well being plugged because a replacement well was drilled? yes Is there an existing well log? yes
 Domestic Irrigation Test Municipal/Industrial Monitor Stock
 If yes, what is replacement well NO? _____ If yes, what is NDWR well log #? 88985

4 EXISTING WELL CONSTRUCTION
 Depth Drilled 640 Feet Depth Cased 640 Feet
 EXISTING CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
18		.375	+1	640

7 WELL PLUGGING PROCEDURE
 Was well cleaned out to total depth? yes no
 If well was not cleaned out to total depth, please explain why: _____
 Was the well contaminated? yes no
 Was the casing pulled? yes no
 Was the casing over drilled? yes no
 If casing was left in place, please show where additional perforations were made:
 Additional Perforations:

Existing Perforations:

Type of perforation	WIRE WRAP SCREEN			
Size of perforation	0.040"			
From <u>320</u> feet to <u>360</u> feet				
From <u>400</u> feet to <u>640</u> feet				
From _____ feet to _____ feet				
From _____ feet to _____ feet				

Type of perforator used: Holt air perforter

From	feet to	feet	Number of perfs per linear foot
From <u>50</u> feet to <u>320</u> feet			<u>8</u> Rows
From <u>360</u> feet to <u>400</u> feet			<u>8</u> Rows
From _____ feet to _____ feet			
From _____ feet to _____ feet			
From _____ feet to _____ feet			
From _____ feet to _____ feet			

5 WATER LEVEL
 Static water level 40 feet below land surface
 Artesian flow _____ G.P.M. _____ P.S.I.
 Water temperature 60 °F Quality good

8 WELL PLUGGING MATERIALS

From	feet to	feet	Material Used	<input type="checkbox"/> Pumped	<input type="checkbox"/> Poured
From <u>30</u> feet to <u>640</u> feet			Bentonite grout	<input checked="" type="checkbox"/>	<input type="checkbox"/>
From <u>1</u> feet to <u>30</u> feet			7 sack cement grout	<input type="checkbox"/>	<input checked="" type="checkbox"/>
From _____ feet to _____ feet				<input type="checkbox"/>	<input type="checkbox"/>
From _____ feet to _____ feet				<input type="checkbox"/>	<input type="checkbox"/>
From _____ feet to _____ feet				<input type="checkbox"/>	<input type="checkbox"/>

6 Additional Notes or Comments
N 41.06930
W 117.56334
N 41.069405
W 117.562240 NAD27
 STATE ENGINEERS OFFICE
 2008 NOV 25 AM 11:07
 RECEIVED

Neat Cement Fluid Weight 15 lbs/gal
 Bentonite Grout 80 % bentonite
 Date Started 11/14/2008
 Date Completed 11/17/2008

9 DRILLER'S CERTIFICATION
 This well was plugged and abandoned under my supervision and the report is true to the best of my knowledge.
 Name Hydro Resources NV Inc dba Humboldt Drilling & Pump Co. Inc.
 Contractor
 Address 4975 W. Winnemucca Blvd.
 Contractor
Winnemucca, Nevada 89445
 Nevada contractor's license number _____
 issued by the State Contractor's Board 56797
 Nevada driller's license number issued by the
 Division of Water Resources, the on-site driller 1713
 Signed S. Tompkins-OFFICE
 By driller performing actual drilling on site or contractor
 Date 11/22/2008