WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

# WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 107577
Permit No. 75468, 75469, 75526
Basin 183

NOTICE OF INTENT NO. 30534

1. OWNER Tuffy Ranch Properties
MAILING ADDRESS 6609 N. Wingfield Parkway Sparks, NV 89436
ADDRESS AT WELL LOCATION 3850 N. Lake Valley Rd Lake Valley NV

2. LOCATION NW ¼ SW ¼ Sec. 22 T. 6 N/S R. 66 E. Lincoln County
PERMIT NO. 75486 T (Issued by Water Resources) | 005-121-09 (Parcel No.) | Subdivision Name

3. WORK PERFORMED
☑ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Abandon ☐ Other

4. PROPOSED USE
☐ Domestic ☑ Irrigation ☐ Test
☐ Municipal/Industrial ☐ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☑ Rotary ☐ RVC
☐ Air ☐ Other

6. LITHOLOGIC LOG

| Material | Water Strata | From | To | Thickness |
|---|---|---|---|---|
| Silt, Sand, Clay | | 0 | 38 | 38 |
| Silt, sand, gravel | | 38 | 231 | 193 |
| Clay | | 231 | 238 | 7 |
| Sand, gravel | | 238 | 371 | 133 |
| Clay | | 371 | 380 | 9 |
| Sand, gravel - Cementation | | 380 | 504 | 124 |

NAD 27
38° 21.754 N
114° 33.657 W

N 38.362582
W 114.560981 NAD27

Date started Apr 30, 2007
Date completed May 15, 2007

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☑ Air Lift

| STATIC WATER LEVEL | Draw Down (Feet Below Static) | Time (Hours) |
|---|---|---|
| 1000 | 60' | 6 hrs |

2009 APR -3 PM 12:05
RECEIVED

8. WELL CONSTRUCTION
Depth Drilled 504 Feet Depth Cased 504 Feet

HOLE DIAMETER (BIT SIZE)

| | | From | To |
|---|---|---|---|
| 24 Inches | | 0 Feet | 504 Feet |
| Inches | | Feet | Feet |
| Inches | | Feet | Feet |

CASING SCHEDULE

| Size O.D. (Inches) | Weight/Ft. (Pounds) | Wall Thickness (Inches) | From (Feet) | To (Feet) |
|---|---|---|---|---|
| 16 | 62.64 | .375 | 0 | 504 |
| | | | | |
| | | | | |

Perforations:
Type perforation Factory milled
Size perforation 3/16 x 2½
From 197 feet to 493 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☑ Yes ☐ No
Depth of Seal 55'
Placement Method: ☐ Pumped ☑ Poured
Seal Type: ☐ Neat Cement ☐ Cement Grout ☑ Concrete Grout
Gravel Packed: ☑ Yes ☐ No
From 55 feet to 504 feet

9. WATER LEVEL
Static water level 105.2 feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature 48 °F Quality Good

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name Webber Drilling (Contractor)
Address PO Box 40 (Contractor)
Overton, NV 89040
Nevada contractor's license number issued by the State Contractor's Board 0025887
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 2238
Signed Bryan Anzalone (By driller performing actual drilling on site or contractor)
Date May 20, 2007

(Rev. 12-01) USE ADDITIONAL SHEETS IF NECESSARY (O)-627