

STATE OF NEVADA  
 DIVISION OF WATER RESOURCES  
**WELL DRILLER'S PLUGGING REPORT**

OFFICE USE ONLY  
 Log No. 107593  
 Permit No. \_\_\_\_\_  
 Basin 108

PRINT OR TYPE ONLY  
 DO NOT WRITE ON BACK

Please complete this form in its entirety in  
 accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 63642

1 OWNER JOE SCEIRINE  
 MAILING ADDRESS PO BOX 1013 YERINGTON, NV 89447  
 SW NW

ADDRESS AT WELL LOCATION SCEIRINE RANCHES  
 Subdivision Name: \_\_\_\_\_ County: Lyon

2 LOCATION NE 1/4 NE 1/4 Sec 3 T 12N N/S R 25 E  
 PERMIT/WAIVER No. 19828 / 60495 Parcel No. 19828  
Issued by Water Resources

Latitude 38.93220 UTM E  NAD 27  
 Longitude 119.17910 N  NAD 83/WGS 84

3 TYPE OF WELL  
 Domestic  Irrigation  Test  
 Municipal/Industrial  Monitor  Stock

Is this well being plugged because a replacement well was drilled? Yes  
 If yes, what is replacement well NOI? 63027  
 Is there an existing well log? Yes  
 If yes, what is NDWR well log #? 48804

4 EXISTING WELL CONSTRUCTION  
 Depth Drilled 450 Feet Depth Cased 440 Feet

EXISTING CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
16	42.05	.250	+1	440

7 WELL PLUGGING PROCEDURE  
 Was well cleaned out to total depth?  yes  no  
 If well was not cleaned out to total depth, please explain why: \_\_\_\_\_  
 Was the well contaminated?  yes  no  
 Was the casing pulled?  yes  no  
 Was the casing over drilled?  yes  no  
 If casing was left in place, please show where additional perforations were made:  
 Additional Perforations: \_\_\_\_\_

Existing Perforations:

Type of perforation	Mill Slot & Louvered
Size of perforation	1/8 x 3
From <u>100</u> feet to <u>440</u> feet	
From _____ feet to _____ feet	
From _____ feet to _____ feet	
From _____ feet to _____ feet	

Hot Air

Type of perforator used:	From	To	Number of perfs per linear foot
	<u>50</u>	<u>100</u>	<u>6 Rows</u>

5 WATER LEVEL  
 Static water level 25 feet below land surface  
 Artesian flow \_\_\_\_\_ G.P.M. P.S.I.  
 Water temperature Cool °F Quality Good

8 WELL PLUGGING MATERIALS

Material Used	From	To	
Cement	<u>0</u>	<u>25</u>	<input type="checkbox"/> Pumped <input checked="" type="checkbox"/> Poured
Bentonite Grout	<u>25</u>	<u>440</u>	<input checked="" type="checkbox"/> Pumped <input type="checkbox"/> Poured
			<input type="checkbox"/> Pumped <input type="checkbox"/> Poured
			<input type="checkbox"/> Pumped <input type="checkbox"/> Poured
			<input type="checkbox"/> Pumped <input type="checkbox"/> Poured

6 Additional Notes or Comments  
N38.932595  
W119.178608 NFD27  
 STATE ENGINEERS OFFICE  
 90-11 HW 61 AON B00Z  
 RECEIVED

Neat Cement Fluid Weight 15 lbs/gal  
 Bentonite Grout 80 % bentonite  
 Date Started 11/4/2008  
 Date Completed 11/6/2008

9 DRILLER'S CERTIFICATION  
 This well was plugged and abandoned under my supervision and the report is true to the best of my knowledge.  
 Name Hydro Resources Inc. dba Humboldt Drilling & Pump Co., Inc.  
Contractor  
 Address 4975 W. Winnemucca Blvd.  
Contractor  
Winnemucca, Nevada 89445  
 Nevada contractor's license number 56797  
issued by the State Contractor's Board  
 Nevada driller's license number issued by the 1713  
Division of Water Resources, the on-site driller  
 Signed [Signature]  
By driller performing actual drilling on site or contractor  
 Date 11/17/2008

USE ADDITIONAL SHEETS IF NECESSARY

Plugs log 5913