STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

OFFICE USE ONLY
Log No. 101594
Permit No.
Basin Ø66

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 61416

1. OWNER Barrick/Pinson Mining Company
MAILING ADDRESS HC66 Box 2
Golconda, NV 89414-9602

ADDRESS AT WELL LOCATION Pinson Mine
Hole #GMWCX-5D
Subdivision Name: County: Humboldt

2. LOCATION NW ¼ NW ¼ Sec 33 T 38N N/S R 42 E
PERMIT/WAIVER No. NEV2ØØ5103, NEV89ØØ2
Issued by Water Resources Parcel No.

Latitude 41.130905 Longitude 117.258455
UTM E 478306 N 4553109
[X] NAD 27 [ ] NAD 83/WGS 84

3. WORKED PERFORMED
[X] New Well [ ] Replace [ ] Recondition
[ ] Deepen [ ] Other

4. PROPOSED USE
[ ] Domestic [ ] Irrigation [ ] Test
[ ] Municipal/Industrial [X] Monitor [ ] Stock

5. WELL TYPE
[ ] Cable [ ] Rotary [X] RVC
[ ] Air [ ] Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Alluvium & Boulders		0	80	80
Black Rock w/ Some Clay		80	620	540
Black Rock		620	810	190
Green Rock (Fractured)		810	825	15
Black Rock		825	1100	275

Date started: 9-Oct, 20 08
Date completed: 20-Oct, 20 08

7. Water Level
Static water level: 450 feet below land surface
Artesian Flow: N/A G.P.M. P.S.I.
Water Temperature: Cool °F
Quality: Milky

8. WELL TEST DATA
TEST METHOD: [ ] Bailer [ ] Pump [X] Air Lift

	G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
1025	60	575	20 min
1100	70	650	20 min

9. WELL CONSTRUCTION
Depth Drilled 1100 Feet Depth Cased 1098 ~~1100~~ Feet

HOLE DIAMETER (BIT SIZE)

		From		To	
14	Inches	0	Feet	80	Feet
9 3/4	Inches	80	Feet	1025	Feet
9 1/2	Inches	1025	Feet	1100	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
4.		Sch. 40	+2	1098

Perforations:
Type of perforation Slotted
Size of perforation 0.03
From 1000 feet to 1080 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Annular Seal: [X] Yes [ ] No
[X] Neat Cement 0 to 50 [X] Pumped [ ] Poured
[ ] Cement Grout to [ ] Pumped [ ] Poured
[ ] Concrete Grout to [ ] Pumped [ ] Poured
[ ] ≥30% Bentonite Grout to [ ] Pumped [ ] Poured
Gravel Pack: [X] Yes [ ] No 1096 to 1100 [ ] Pumped [X] Poured
Type: # 8 Sand
Bentonite Chips: [X] Yes [ ] No 50 to 1096 [ ] Pumped [X] Poured
Type: 3/8" Chips Hole Plug

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name Eklund Drilling Company, Inc. (Contractor)
Address PO Box 2748 (Contractor)
Elko, NV 89803
Nevada contractor's license number issued by the *State Contractor's Board* 0030823
Nevada driller's license number issued by the Division of Water Resources, the *on-site driller* M-2260
Signed Reese Schoorl by [illegible] (By driller performing actual drilling on site or contractor)
Date 10/20/2008

RECEIVED 2008 NOV 18 AM 10:38 STATE ENGINEER'S OFFICE

(Rev. 05-06)

USE ADDITIONAL SHEETS IF NECESSARY