STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S REPORT

OFFICE USE ONLY
Log No. 107670
Permit No.
Basin Ø66

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 61422

1. OWNER Newmont Mining Corp.
MAILING ADDRESS PO Box 69
Golconda, NV 89414

ADDRESS AT WELL LOCATION Twin Creeks Mine
Hole #TM-50002 (TM-10002 on NOI)
Subdivision Name: County: Humboldt RC 4-11-09

2. LOCATION NW ¼ SW ¼ Sec 10 T 39N N/S R 43 E
PERMIT/WAIVER No. M/O-1497
Issued by Water Resources Parcel No.

Latitude 41.272938
Longitude 117.122459
UTM E 489743.3539 [X] NAD 27
N 4568851.3849 [ ] NAD 83/WGS 84

3. WORKED PERFORMED
[X] New Well [ ] Replace [ ] Recondition
[ ] Deepen [ ] Other

4. PROPOSED USE
[ ] Domestic [ ] Irrigation [ ] Test
[ ] Municipal/Industrial [X] Monitor [ ] Stock

5. WELL TYPE
[ ] Cable [ ] Rotary [ ] RVC
[X] Air [ ] Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Gravels		0	55	55
Sand		55	70	15
Sany Gravels		70	150	80
Clay & Sand		150	180	30
Sandy Clays		180	295	115
Gravels	106PM	295	320	25
Sand & Gravels		320	340	20
Clays	206PM	340	360	20
Gravels		360	380	20
Clays		380	500	120
Gravels		500	510	10
Limestone	606PM	510	700	190

Date started: 25-Sep , 20 08
Date completed: 30-Sep , 20 08

9. WELL CONSTRUCTION
Depth Drilled 700 Feet Depth Cased 700 Feet

HOLE DIAMETER (BIT SIZE)

		From		To	
9 5/8	Inches	0	Feet	15	Feet
6 3/4	Inches	15	Feet	700	Feet
	Inches		Feet		Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
2.5	PVC	.250	+2	700

Perforations:
Type of perforation Slotted
Size of perforation 0.02
From 630 feet to 700 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Annular Seal: [X] Yes [ ] No
[X] Neat Cement 51 to 0 [X] Pumped [ ] Poured
[ ] Cement Grout to [ ] Pumped [ ] Poured
[ ] Concrete Grout to [ ] Pumped [ ] Poured
[ ] ≥30% Bentonite Grout to [ ] Pumped [ ] Poured

Gravel Pack: [X] Yes [ ] No 700 to 629 [ ] Pumped [X] Poured
Type: #12 Silica Sand
Bentonite Chips: [X] Yes [ ] No 629 to 51 [ ] Pumped [X] Poured
Type: 3/8" Hole Plug

7. Water Level
Static water level: 424 feet below land surface
Artesian Flow: No G.P.M. N/A P.S.I.
Water Temperature: Cool °F
Quality: Good

8. WELL TEST DATA
TEST METHOD: [ ] Bailer [ ] Pump [ ] Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)

STATE ENGINEERS OFFICE
2008 OCT 20 PM 12:42
RECEIVED

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name Eklund Drilling Company, Inc.
Contractor
Address PO Box 2748
Contractor
Elko, NV 89803
Nevada contractor's license number issued by the *State Contractor's Board* 0030823
Nevada driller's license number issued by the Division of Water Resources, the *on-site driller* 1777
Signed Dennis White by
By driller performing actual drilling on site or contractor
Date 10/15/2008

(Rev. 05-06)
USE ADDITIONAL SHEETS IF NECESSARY