

STATE OF NEVADA  
DIVISION OF WATER RESOURCES  
WELL DRILLER'S PLUGGING REPORT

OFFICE USE ONLY  
Log No. 107933  
Permit No. \_\_\_\_\_  
Basin 212

PRINT OR TYPE ONLY  
DO NOT WRITE ON BACK

Please complete this form in its entirety in  
accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 34859

1 OWNER Public Right of Way (Clark County)  
MAILING ADDRESS 5857 E. Flamingo Rd., LV, NV 89122

ADDRESS AT WELL LOCATION Cabana Rd (300' North of Flamingo Rd.)

Subdivision Name: Cabana Relief Interceptor County: Clark

2 LOCATION SW ¼ SE ¼ Sec 16 T 21S N/S R 62 E  
PERMIT/WAIVER No. DW 1256 161-16-899-001  
Issued by Water Resources Parcel No.

Latitude \_\_\_\_\_ UTM E SEE  NAD 27  
Longitude \_\_\_\_\_ N ATTACHED  NAD 83/WGS 84

3 Temp de-watering  
 Domestic  Irrigation  Test  
 Municipal/Industrial  Monitor  Stock

Is this well being plugged because a replacement well was drilled? no  
If yes, what is replacement well NOI? \_\_\_\_\_  
Is there an existing well log? yes  
If yes, what is NDWR well log #? \_\_\_\_\_

4 EXISTING WELL CONSTRUCTION  
Depth Drilled 30 Feet Depth Cased 30 Feet

7 WELL PLUGGING PROCEDURE  
Was well cleaned out to total depth?  yes  no

EXISTING CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
8	6	3/8	0	30

If well was not cleaned out to total depth, please explain why: \_\_\_\_\_  
Was the well contaminated?  yes  no  
Was the casing pulled?  yes  no  
Was the casing over drilled?  yes  no

Existing Perforations:  
Type of perforation machine slot  
Size of perforation 0.032  
From 10 feet to 30 feet  
From \_\_\_\_\_ feet to \_\_\_\_\_ feet

If casing was left in place, please show where additional perforations were made:  
Additional Perforations:  
Type of perforator used: \_\_\_\_\_  
From \_\_\_\_\_ feet to \_\_\_\_\_ feet Number of perfs per linear foot \_\_\_\_\_  
From \_\_\_\_\_ feet to \_\_\_\_\_ feet Number of perfs per linear foot \_\_\_\_\_  
From \_\_\_\_\_ feet to \_\_\_\_\_ feet Number of perfs per linear foot \_\_\_\_\_  
From \_\_\_\_\_ feet to \_\_\_\_\_ feet Number of perfs per linear foot \_\_\_\_\_  
From \_\_\_\_\_ feet to \_\_\_\_\_ feet Number of perfs per linear foot \_\_\_\_\_  
From \_\_\_\_\_ feet to \_\_\_\_\_ feet Number of perfs per linear foot \_\_\_\_\_

5 WATER LEVEL  
Static water level 8 feet below land surface  
Artesian flow n/a G.P.M. \_\_\_\_\_ P.S.I. \_\_\_\_\_  
Water temperature n/a °F Quality \_\_\_\_\_

8 WELL PLUGGING MATERIALS  
Material Used  
From 0 feet to 10 feet neat cement  Pumpe  Poured  
From \_\_\_\_\_ feet to \_\_\_\_\_ feet  Pumped  Poured

6 Additional Notes or Comments

Abandoned all 6 wells

**DCNR/DWR  
RECEIVED  
JAN 23 2008**

**LAS VEGAS OFFICE**

Neat Cement Fluid Weight 94/5 lbs/gal  
Bentonite Grout \_\_\_\_\_ % bentonite  
Date Started 12/20/2007  
Date Completed 12/20/2007

9 DRILLER'S CERTIFICATION  
This well was plugged and abandoned under my supervision and the report is true to the best of my knowledge.  
Name Viking Drillers Inc Contractor  
Address 801 Northport Dr. Contractor  
West Sacramento, CA 95691  
Nevada contractor's license number \_\_\_\_\_ issued by the State Contractor's Board 0034680  
Nevada driller's license number issued by the Division of Water Resources, the on-site driller \_\_\_\_\_ M 2091  
Signed [Signature]  
Date 1/16/2008  
By driller performing actual drilling on site or contractor

**Dewater**

**From:** Matt Thompson(LV) [mthompson@ConverseConsultants.com]  
**Sent:** Friday, December 28, 2007 3:04 PM  
**To:** SLachapelle@VikingDrillersInc.com  
**Subject:** GPS Locations for Cabana Rd. Las Vegas

Log # 15  
107928 to  
107933

Sean,

Here are the GPS coordinates you requested for the (6) well locations on Cabana Road, Las Vegas, Nevada. I will forward you the log diagrams pending their completion. If you have any other questions please feel free to contact me. Thanks.

	Northing	Easting
W-1:	26744313.2600	811962.89470
W-2:	26744372.2100	811957.40000
W-3:	26744383.6900	811936.66550
W-4:	26744425.5400	811945.89580
W-5:	26744509.2200	811954.52700
W-6:	26744605.4700	811962.96880

**Matt Thompson**  
Staff Geologist

**Converse Consultants**

731 Pilot Road, Suite H  
Las Vegas, NV 89119  
phone (702) 269-8336 ext. 2065  
cell (702) 506-2149  
fax (702) 269-8353

[MThompson@converseconsultants.com](mailto:MThompson@converseconsultants.com)

The information contained in this e-mail message (including attachments) is intended only for the personal and confidential use of the recipient(s) named above. This message (including attachments) may be work product and as such is privileged and confidential. If the reader of this message is not the intended recipient or agent responsible for delivering it to the intended recipient, you are hereby notified that you have received this document in error and that any review, dissemination, distribution, or copying of this message is strictly prohibited. If you have received this communication in error, please notify us immediately by e-mail, and delete the original message.

DCNR/DWR  
RECEIVED  
JAN 23 2008

LAS VEGAS OFFICE

THIS BORING LOG IS FOR VIKING'S INTERNAL PURPOSES ONLY. IT DOES NOT REPRESENT INFORMATION PROVIDED BY A SOILS ENGINEER.

LOG FOR BORING NO. <b>6 I</b>		JOB NAME: <b>CONVERSE COAL</b>			
DATE STARTED <b>12-11-07</b>	DATE COMPLETED <b>12-12-07</b>	LOGGED BY <b>Ed</b>	DRILLED BY <b>Ed</b>	TYPE OF DRILL RIG <b># 36</b>	JOB NO. <b>1056</b>
DEPTH OF HOLE <b>30'</b>	DIAMETER OF HOLE <b>24"</b>	CASING <b>8"</b>	PERFORATIONS <b>20'</b>	SAMPLING METHOD	ELEVATION

LOCATION

DRILLERS NOTES:

**29**

DEPTH	SAMPLES	GRAPHIC	DESCRIPTION
			street base
			cobble
			red clay
10'			silt sand
			hard clay
20'			
30'			
40'			
50'			
60'			
70'			
80'			
90'			
100'			

**DCNR/DWR  
RECEIVED  
JAN 23 2008  
LAS VEGAS OFFICE**

THIS BORING LOG IS FOR VIKING'S INTERNAL PURPOSES ONLY. IT DOES NOT REPRESENT INFORMATION PROVIDED BY A SOILS ENGINEER.

LOG FOR BORING NO. <u>5-2,74</u>		JOB NAME: <u>CONVERSE CAN</u>			
DATE STARTED <u>12-11-07</u>	DATE COMPLETED <u>12-12-07</u>	LOGGED BY <u>Ed</u>	DRILLED BY <u>Ed</u>	TYPE OF DRILL RIG <u>#36</u>	JOB NO. <u>1056</u>
DEPTH OF HOLE <u>30'</u>	DIAMETER OF HOLE <u>24"</u>	CASING <u>8"</u>	PERFORATIONS <u>20'</u>	SAMPLING METHOD	ELEVATION

LOCATION  
see back

DRILLERS NOTES:  
29

DEPTH	SAMPLES	GRAPHIC	DESCRIPTION
			<del>street base rock</del>
			cobble
			red clay
10'			silty sand
			hard red clay
20'			
30'			
40'			
50'			
60'			
70'			
80'			
90'			
100'			

DCNR/DWR  
RECEIVED  
JAN 23 2008  
LAS VEGAS OFFICE