

**STATE OF NEVADA  
DIVISION OF WATER RESOURCES  
WELL DRILLER'S REPORT**

OFFICE USE ONLY

Log No. 108015  
Permit No. \_\_\_\_\_  
Basin DES

**PRINT OR TYPE ONLY  
DO NOT WRITE ON BACK**

*Please complete this form in its entirety in  
accordance with NRS 534.170 and NAC 534.340*

NOTICE OF INTENT NO. 63477

1. OWNER Pyramid Lake Fisheries  
MAILING ADDRESS Star Route, Sutcliffe NV 89510

ADDRESS AT WELL LOCATION 100 Numana Rd  
Wadsworth, NV

2. LOCATION NE 1/4 NE 1/4 Sec 6 T 21N N/S R 24 E  
PERMIT/WAIVER No. 079-180-42  
Issued by Water Resources  
Parcel No. \_\_\_\_\_

Subdivision Name: \_\_\_\_\_ County: Washoe  
Latitude 39.72136 UTM E  NAD 27  
Longitude 119.32344 N  NAD 83/WGS 84

3. WORKED PERFORMED  
 New Well  Replace  Recondition  
 Deepen  Other

4. PROPOSED USE  
 Domestic  Irrigation  Test  
 Municipal/Industrial  Monitor  Stock

5. WELL TYPE  
 Cable  Rotary  RVC  
 Air  Other  x mud

6. LITHOLOGIC LOG				
Material	Water Strata	From	To	Thick-ness
sand & gravel & clay		0	21	21
sand & gravel	x	21	78	57
clay		78	84	6
sand & gravel	x	84	110	26
clay		110	112	2
sand & gravel	x	112	162	50
clay		162	173	11
gravel & clay	x	173	220	47
clay		220	275	55
gravel	x	275	290	15
clay		290	312	22
sand & gravel	x	312	328	16
clay		328	338	10

9. WELL CONSTRUCTION				
Depth Drilled	Feet	Depth Cased	Feet	
338		338		
HOLE DIAMETER (BIT SIZE)				
20	Inches	0	Feet	338
	Inches		Feet	
	Inches		Feet	

CASING SCHEDULE				
Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
10 5/8	40.48	.312	+2	338

Perforations:				
Type of perforation	Size of perforation	From	feet to	
screen	.050"	58	feet to	158
		178	feet to	218
		318	feet to	338
			feet to	
			feet to	

Annular Seal:  Yes  No

Neat Cement to \_\_\_\_\_  Pumped  Poured

Cement Grout 0 to 50  Pumped  Poured

Concrete Grout to \_\_\_\_\_  Pumped  Poured

≥30% Bentonite Grout to \_\_\_\_\_  Pumped  Poured

Gravel Pack:  Yes  No 50 to 338  Pumped  Poured

Type: \_\_\_\_\_

Bentonite Chips:  Yes  No \_\_\_\_\_ to \_\_\_\_\_  Pumped  Poured

Type: \_\_\_\_\_

Date started: 12-Jan, 20 09  
Date completed: 3-Feb, 20 09

7. Water Level  
Static water level: 60 feet below land surface  
Artesian Flow: \_\_\_\_\_ G.P.M. \_\_\_\_\_ P.S.I.  
Water Temperature: cool °F  
Quality: clear

8. WELL TEST DATA			
TEST METHOD:	G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
<input type="checkbox"/> Bailor <input type="checkbox"/> Pump <input checked="" type="checkbox"/> Air Lift	300+	278	10

10. DRILLER'S CERTIFICATION  
This well was drilled under my supervision and the report is true to the best of my knowledge.

Name McKay Drilling, Inc  
Contractor

Address 4850 Joule St. Suite A5  
Contractor

Reno, NV 89502

Nevada contractor's license number \_\_\_\_\_  
issued by the State Contractor's Board 14170

Nevada driller's license number issued by the \_\_\_\_\_  
Division of Water Resources, the on-site driller 2121

Signed Steve McKay  
By driller performing actual drilling on site or contractor

Date 2/25/2009

(Rev. 05-00)

**USE ADDITIONAL SHEETS IF NECESSARY**