WHITE - DIVISION OF WATER RESOURCES
CANARY - CLIENT'S COPY
PINK - WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 108103
Permit No. 73322
Basin 062

NOTICE OF INTENT NO. 56566

WELL No. 6 - SECTION 15 DDBB1

1. OWNER BAROID DRILLING FLUIDS
MAILING ADDRESS 912 DUNPHY ROAD
BATTLE MOUNTAIN, NV 89820-9500

ADDRESS AT WELL LOCATION ROSSI MINE PIT

2. LOCATION SE 1/4 SE 1/4 Sec. 15 T 37N N/S R 49E E ELKO County
PERMIT NO. 73322 (Issued by Water Resources) Parcel No. Subdivision Name

3. WORK PERFORMED: New Well [X] Replace [ ] Recondition [ ] Deepen [ ] Abandon [ ] Other

4. PROPOSED USE: [ ] Domestic [ ] Irrigation [ ] Test [X] Municipal/Industrial [ ] Monitor [ ] Stock

5. WELL TYPE: [ ] Cable [X] Rotary RVC [X] Air [ ] Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
BRN ASH		0	80	80
BRN ASH W/BRN CLAY	X	80	100	20
BLK CHERT		100	145	45
BLK & RED CHERT	X	145	200	55
RED CHERT W/GREY SHALE	X	200	230	30
BLK CHERT W/BRN CHERT		230	330	100
BRN CHERT FRACTURED	X	330	350	20
BLK CHERT		350	380	30
BLK & BRN CHERT		380	400	20

A METAL PLATE WAS WELDED ON TOP OF THE CASING TO PREVENT ACCESS - A 2" PORT WAS WELD TO THE SURFACE CASING

Plugged by Well log #120487

Date started 10/18/2005, 19__
Date completed 10/21/2005, 19__

7. WELL TEST DATA

TEST METHOD: [ ] Bailer [ ] Pump [X] Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
38		3

STATE E
MAY 21 2008

8. WELL CONSTRUCTION
Depth Drilled 400 Feet Depth Cased 400 Feet

HOLE DIAMETER (BIT SIZE)

		From		To	
11	Inches	0	Feet	400	Feet
	Inches		Feet		Feet
	Inches		Feet		Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
6.625	13	.188	+1	60
6.625			60	400

Perforations:
Type perforation CERT LOC PVC SDR17
Size perforation .01
From 60 feet to 400 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: [X] Yes [ ] No
Depth of Seal 50
Placement Method: [X] Pumped [ ] Poured
Seal Type: [X] Neat Cement [ ] Cement Grout [ ] Concrete Grout

Gravel Packed: [X] Yes [ ] No
From 50 feet to 400 feet

9. WATER LEVEL
Static water level 62 feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature °F Quality

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.

Name HACKWORTH DRILLING, INC (Contractor)
Address P.O.BOX 850 (Contractor)
ELKO,NV 89803
Nevada contractor's license number issued by the State Contractor's Board 020592
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1998
Signed Bradley D. Wiest (By driller performing actual drilling on-site or contractor)
Date 10/22/2005

USE ADDITIONAL SHEETS IF NECESSARY

FACSIMILE RCVD