


STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S PLUGGING REPORT



OFFICE USE ONLY 108558

Log No. _____
Permit No. _____
Basin 179

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 58072

1 OWNER Nevada Department of Wildlife
MAILING ADDRESS HCR 10 Box 10808
Ely, NV, 89301

ADDRESS AT WELL LOCATION Stepptoe Valley Wildlife Mgt. Area
Ely, NV.
Subdivision Name: _____ County: White Pine

2 LOCATION NE 1/4 NW 1/4 Sec 17 T 15N N/S R 64 E
PERMIT/WAIVER No. _____
Issued by Water Resources Parcel No.

Latitude 39°10.361N UTM E NAD 27
Longitude 114°48.647W N NAD 83/WGS 84

3 TYPE OF WELL
 Domestic Irrigation Test
 Municipal/Industrial Monitor Stock

Is this well being plugged because a replacement well was drilled? no
If yes, what is replacement well NO? _____

Is there an existing well log? yes
If yes, what is NDWR well log #? 3279

4 EXISTING WELL CONSTRUCTION
Depth Drilled 43 Feet Depth Cased 40 Feet

7 WELL PLUGGING PROCEDURE
Was well cleaned out to total depth? yes no

EXISTING CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
6"		10 gage	+2'	40'

If well was not cleaned out to total depth, please explain why: _____
Was the well contaminated? yes no
Was the casing pulled? yes no
Was the casing over drilled? yes no

Existing Perforations:

Type of perforation	Size of perforation	From	To
torch slot	1/8" x 12"		

If casing was left in place, please show where additional perforations were made:
Additional Perforations:

Type of perforater used:	From	To	Number of perms per linear foot
Mills Knife	18	surface	6

5 WATER LEVEL
Static water level 16.22 feet below land surface
Artesian flow _____ G.P.M. P.S.I.
Water temperature _____ °F Quality _____

8 WELL PLUGGING MATERIALS

From	To	Material Used	neat cement	Pumped	Poured
40	surface		<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

6 Additional Notes or Comments

Measured static water level at a depth of 16.22' and depth of well at 35'. Blew debris from well to depth of 40.5'. Installed 6" Mills Knife and perforated 6 rows per foot from 18' back to surface. We then installed 35' of 2" tremme pipe and then mixed 13 bags of Portland Type II cement with approx. 70 gallons of water and pumped through tremme pipe from bottom of well to the surface. Actual casing volume should have required 8 cubic feet but actually used 13 cubic feet.

39.172743 N
114.809935 W
NAD 27 (TA)

STATE ENGINEERS OFFICE
2009 SEP 14 AM 11:52
RECEIVED

From _____ feet to _____ feet Pumped Poured
From _____ feet to _____ feet Pumped Poured

Neat Cement Fluid Weight _____ lbs/gal
Bentonite Grout _____ % bentonite
Date Started 9/2/2009
Date Completed 9/2/2009

9 DRILLER'S CERTIFICATION
This well was plugged and abandoned under my supervision and the report is true to the best of my knowledge.

Name Carson Pump LLC Contractor
Address P.O. Box 20159 Contractor
Carson City, NV, 89721
Nevada contractor's license number issued by the State Contractor's Board 39920A
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 2265
Signed [Signature]
Date 9/9/2009
By driller performing actual drilling on site or contractor

USE ADDITIONAL SHEETS IF NECESSARY

(Rev. 05-08)