

STATE OF NEVADA  
DIVISION OF WATER RESOURCES  
WELL DRILLER'S PLUGGING REPORT

OFFICE USE ONLY

Log No. 108042  
Permit No. \_\_\_\_\_  
Basin 0609



PRINT OR TYPE ONLY  
DO NOT WRITE ON BACK

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 63021

1 OWNER Winnemucca Farms ADDRESS AT WELL LOCATION Winnemucca Farms Well #16  
MAILING ADDRESS One Potato Rd  
Winnemucca, NV 89445 Subdivision Name: \_\_\_\_\_ County: Humboldt

2 LOCATION SE 1/4 SW 1/4 Sec 31 T 39N N/S R 39 E Latitude 41° 12.713 N UTM E  NAD 27  
PERMIT/WAIVER No. 25946 Longitude 117° 37.850 W N  NAD 83/WGS 84  
*Issued by Water Resources Parcel No.*

3 TYPE OF WELL  
 Domestic  Irrigation  Test  
 Municipal/Industrial  Monitor  Stock  
Is this well being plugged because a replacement well was drilled? YES  
If yes, what is replacement well NOI? 63022  
Is there an existing well log? YES  
If yes, what is NDWR well log #? 41703

4 EXISTING WELL CONSTRUCTION  
Depth Drilled 492' Feet Depth Cased 492' Feet

EXISTING CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
16"		.250"	0'	492'

7 WELL PLUGGING PROCEDURE  
Was well cleaned out to total depth?  yes  no  
If well was not cleaned out to total depth, please explain why: \_\_\_\_\_  
Was the well contaminated?  yes  no  
Was the casing pulled?  yes  no  
Was the casing over drilled?  yes  no  
If casing was left in place, please show where additional perforations were made: \_\_\_\_\_

Existing Perforations:

Type of perforation	Size of perforation	From	To
WIRE WRAP SCREEN	0.040"		
		From 205'	feet to 265' feet
		From 325'	feet to 365' feet
		From 375'	feet to 415' feet
		From 470'	feet to 480' feet

Additional Perforations:

Type of perforator used:	From	To	Number of perfs per linear foot
Holt Air Perforator	From 50'	feet to 205' feet	8 ROW
	From 265'	feet to 325' feet	8 ROW
	From 365'	feet to 375' feet	8 ROW
	From 415'	feet to 470' feet	8 ROW
	From 480'	feet to 492' feet	8 ROW

5 WATER LEVEL  
Static water level 85' feet below land surface  
Artesian flow \_\_\_\_\_ G.P.M. \_\_\_\_\_ P.S.I.  
Water temperature \_\_\_\_\_ °F Quality \_\_\_\_\_

8 WELL PLUGGING MATERIALS

From	To	Material Used	Method
From 0'	feet to 20' feet	NEAT CEMENT	<input checked="" type="checkbox"/> Pumped <input type="checkbox"/> Poured
From 20'	feet to 492' feet	GOPHER GROUT	<input checked="" type="checkbox"/> Pumped <input type="checkbox"/> Poured
From _____	feet to _____ feet		<input type="checkbox"/> Pumped <input type="checkbox"/> Poured
From _____	feet to _____ feet		<input type="checkbox"/> Pumped <input type="checkbox"/> Poured
From _____	feet to _____ feet		<input type="checkbox"/> Pumped <input type="checkbox"/> Poured

6 Additional Notes or Comments

41.211982° N  
117.629872° W  
NAD 27  
Plugging well log #41703  
(TA)

11:11:11 41 703 6002

Neat Cement Fluid Weight 15 LBS lbs/gal  
Bentonite Grout 20% % bentonite  
Date Started 7-Jun-09  
Date Completed 12-Jun-09

9 DRILLER'S CERTIFICATION  
This well was plugged and abandoned under my supervision and the report is true to the best of my knowledge.  
Name Hydro Resources Nevada Inc dba Humboldt Drilling & Pump  
Contractor  
Address 4975 W. Winnemucca Blvd.  
Contractor  
Winnemucca, NV 89445  
Nevada contractor's license number 56797  
issued by the State Contractor's Board  
Nevada driller's license number issued by the # 1713  
Division of Water Resources, the on-site driller  
Signed Charlye James - Office  
By driller performing actual drilling on site or contractor  
Date 7/13/2009