STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S REPORT

OFFICE USE ONLY
Log No. 108646
Permit No.
Basin 131

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 61101

1. OWNER Newmont Mining Corp.
MAILING ADDRESS PO Box 388
NE Valmy, NV 89438

ADDRESS AT WELL LOCATION Mule Canyon
Hole #MU-1364
Subdivision Name: County: Lander

2. LOCATION SW ¼ NE ¼ Sec 3 T 31N N/S R 47 E
PERMIT/WAIVER No. SE
Issued by Water Resources Parcel No.

Latitude
Longitude
UTM E 529064 [x] NAD 27
N 4492852 [ ] NAD 83/WGS 84

3. WORKED PERFORMED
[x] New Well [ ] Replace [ ] Recondition
[ ] Deepen [ ] Other

4. PROPOSED USE
[ ] Domestic [ ] Irrigation [ ] Test
[ ] Municipal/Industrial [x] Monitor [ ] Stock

5. WELL TYPE
[ ] Cable [ ] Rotary [x] RVC
[ ] Air [ ] Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Sand & Course Gravel		0	20	20
Bed Rock		20	22	2

40.587853°N
116.656558°W
NAD27
(+A)

Date started: 19-May, 20 09
Date completed: 20-May, 20 09

9. WELL CONSTRUCTION
Depth Drilled 22 Feet Depth Cased 22 Feet

HOLE DIAMETER (BIT SIZE)

		From		To	
12 3/4	Inches	0	Feet	5	Feet
8 3/4	Inches	5	Feet	22	Feet
	Inches		Feet		Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
4.5		Sch 80	0	22

Perforations:
Type of perforation Slot
Size of perforation 0.02
From 12 feet to 22 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Annular Seal: [x] Yes [ ] No
[x] Neat Cement 0 to 10 [ ] Pumped [x] Poured
[ ] Cement Grout to [ ] Pumped [ ] Poured
[ ] Concrete Grout to [ ] Pumped [ ] Poured
[ ] ≥30% Bentonite Grout to [ ] Pumped [ ] Poured
Gravel Pack: [x] Yes [ ] No 11 to 22 [ ] Pumped [x] Poured
Type: #8 Sand
Bentonite Chips: [x] Yes [ ] No 10 to 11 [ ] Pumped [ ] Poured
Type: 3/8" Hole Plug

7. Water Level
Static water level: Dry feet below land surface
Artesian Flow: No G.P.M. N/A P.S.I.
Water Temperature: N/A °F
Quality: N/A

8. WELL TEST DATA
TEST METHOD: [ ] Bailer [x] Pump [ ] Air Lift

	G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
100 Gallons	20 gpm		

STATE ENGINEER'S OFFICE
2009 JUN 15 PM 12:11

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name Eklund Drilling Company, Inc. (Contractor)
Address PO Box 2748 (Contractor)
Elko, NV 89803
Nevada contractor's license number issued by the State Contractor's Board ~~0073086~~ 38823
Nevada driller's license number issued by the Division of Water Resources, the on-site driller M2290
Signed Rory Sandstrom by MR (by driller performing actual drilling on site or contractor)
Date 5/20/2009

(Rev. 05-06)

USE ADDITIONAL SHEETS IF NECESSARY