STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S REPORT

OFFICE USE ONLY
Log No. 108749
Permit No.
Basin Ø48

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 64846

1. OWNER JOHN & CAROLYN PERL
MAILING ADDRESS 1869 QUAIL LANE
CARSON CITY, NV 89701-9304

ADDRESS AT WELL LOCATION MOUNTAIN VIEW DRIVE
LOT 9, BLOCK J
Subdivision Name: WESTERN HILLS County: ELKO

2. LOCATION NW ¼ NE ¼ Sec 3 T 32N N/S R 55 E
PERMIT/WAIVER No. 077-010-009
Issued by Water Resources Parcel No.

Latitude 40.692906°N
Longitude 115.761284°W
NAD 27 (A)
UTM E 11T 0604664 ☒ NAD 27
N 4505194 ☐ NAD 83/WGS 84

3. WORKED PERFORMED
☒ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Other

4. PROPOSED USE
☒ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☐ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☒ Rotary ☐ RVC
☒ Air ☐ Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
TOPSOIL		0	1	1
THICK TAN CLAY		1	140	139
FINE GRAVEL	X	140	160	20
COARSE GRAVEL	XX	160	180	20

Date started: 14-Sep, 20 09
Date completed: 14-Sep, 20 09

9. WELL CONSTRUCTION
Depth Drilled 180 Feet Depth Cased 180 Feet

HOLE DIAMETER (BIT SIZE)

		From		To	
10 5/8	Inches	0	Feet	180	Feet
	Inches		Feet		Feet
	Inches		Feet		Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
6.625	13	.188	+2	180

Perforations:
Type of perforation MACHINED MILL SLOT
Size of perforation 3/16" X 3", 6 ROWS
From 160 feet to 180 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Annular Seal: ☒ Yes ☐ No
☒ Neat Cement 3 to 16 ☐ Pumped ☒ Poured
☐ Cement Grout to ☐ Pumped ☐ Poured
☐ Concrete Grout to ☐ Pumped ☐ Poured
☐ ≥30% Bentonite Grout to ☐ Pumped ☐ Poured

Gravel Pack: ☒ Yes ☐ No 50 to 180 ☐ Pumped ☒ Poured
Type: 3/8" WASHED PEA GRAVEL
Bentonite Chips: ☒ Yes ☐ No 16 to 50 ☐ Pumped ☒ Poured
Type: 3/8" BENTONITE CHIPS

7. Water Level
Static water level: 45 feet below land surface
Artesian Flow: G.P.M. P.S.I.
Water Temperature: COLD °F
Quality: GOOD

8. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☒ Air Lift

	G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
825 CFM @ 125 PSI	20		2

STATE ENGINEERS OFFICE
2009 SEP 18 AM 11:14
RECEIVED

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name HACKWORTH DRILLING, INC. (Contractor)
Address P. O. BOX 850 (Contractor)
ELKO, NV 89803
Nevada contractor's license number issued by the *State Contractor's Board* 020582
Nevada driller's license number issued by the Division of Water Resources, the *on-site driller* 1653
Signed (By driller performing actual drilling on site or contractor)
Date 9/15/2009

(Rev. 05-06)

USE ADDITIONAL SHEETS IF NECESSARY