

STATE OF NEVADA
 DIVISION OF WATER RESOURCES
WELL DRILLER'S PLUGGING REPORT

OFFICE USE ONLY **108904**

Log No. _____
 Permit No. _____
 Basin **962**

PRINT OR TYPE ONLY
 DO NOT WRITE ON BACK

Please complete this form in its entirety in
 accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 61116

1 OWNER Rodeo Creek Gold Inc.
 MAILING ADDRESS 4000 W. Winnemucca Blvd
Winnemucca, NV 89445

ADDRESS AT WELL LOCATION Hollister Mine
 Subdivision Name: _____ County: Elko

2 LOCATION NE 1/4 NW 1/4 Sec 9 T 37N N/S R 48 E
 PERMIT/WAIVER No. _____
Issued by Water Resources Parcel No.

Latitude 41° 06' 20" N UTM E NAD 27
 Longitude 116° 33' 40" W N NAD 83/WGS 84

3 TYPE OF WELL
 Domestic Irrigation Test
 Municipal/Industrial Monitor Stock

Is this well being plugged because a replacement well was drilled? Yes
 If yes, what is replacement well NOI? 102141

Is there an existing well log? Yes
 If yes, what is NDWR well log #? 102141

4 EXISTING WELL CONSTRUCTION
 Depth Drilled 200 Feet Depth Cased 190 Feet

7 WELL PLUGGING PROCEDURE
 Was well cleaned out to total depth? yes no
 If well was not cleaned out to total depth, please explain why: _____

EXISTING CASING SCHEDULE				
Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
10.75	28.04	.250	0	120
4.5	2.060	.237	+1	190

Was the well contaminated? yes no
 Was the casing pulled? yes no
 Was the casing over drilled? yes no
 If casing was left in place, please show where additional perforations were made:
 Additional Perforations:
 Type of perforator used: None

Existing Perforations:

Type of perforation	Size of perforation	From	To
Slotted	0.04	130 feet	185 feet

From	feet to	feet	Number of perfs per linear foot

5 WATER LEVEL
 Static water level 137 feet below land surface
 Artesian flow No G.P.M. N/A P.S.I.
 Water temperature Cool °F Quality Good

8 WELL PLUGGING MATERIALS

From	feet to	feet	Material Used	<input type="checkbox"/> Pumped	<input type="checkbox"/> Poured
190	20	20	Super Plug	<input checked="" type="checkbox"/>	<input type="checkbox"/>
20	0	0	Neat Cement	<input checked="" type="checkbox"/>	<input type="checkbox"/>
				<input type="checkbox"/>	<input type="checkbox"/>
				<input type="checkbox"/>	<input type="checkbox"/>
				<input type="checkbox"/>	<input type="checkbox"/>
				<input type="checkbox"/>	<input type="checkbox"/>
				<input type="checkbox"/>	<input type="checkbox"/>

6 Additional Notes or Comments
Pumped Abandonite slurry from bottom of hole to surface.
Allow to settle. Bridge hole one bag hole plug, chip @ 20'
cement to surface, cut monument at surface.

Neat Cement Fluid Weight 15.3 lbs/gal
 Bentonite Grout _____ % bentonite
 Date Started 9/1/2009
 Date Completed 9/1/2009

2009 OCT 13 AM 11:33
 STATE ENGINEER'S OFFICE
41.105556° N
116.561111° W
NOV 27 (70)

9 DRILLER'S CERTIFICATION
 This well was plugged and abandoned under my supervision and the report is true to the best of my knowledge.
 Name Boart Longyear Nevada Contractor
 Address PO Box 2748 Contractor
Elko, NV 89803
 Nevada contractor's license number 0021976
 issued by the State Contractor's Board 0073000
 Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1777
 Signed Dennis L. White by [Signature]
 Date 9/29/2009