

PRINT OR TYPE ONLY  
DO NOT WRITE ON BACK

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

Log No. \_\_\_\_\_  
Permit No. \_\_\_\_\_  
Basin 007

NOTICE OF INTENT NO. 6311  
ADDRESS AT WELL LOCATION 32 miles EAST

1. OWNER Bill Kennedy  
MAILING ADDRESS 235 Red Stone DR  
Reno NV 89512  
2. LOCATION SW 1/4 SE 1/4 Sec. 10 T. 44  
PERMIT NO. 78177 061-110-18

ADDRESS AT WELL LOCATION of VY19, Nevada  
County Washoe  
Parcel No. \_\_\_\_\_  
Subdivision Name \_\_\_\_\_

3. WORK PERFORMED  
 New Well  Replace  Recondition  
 Deepen  Abandon  Other \_\_\_\_\_

4. PROPOSED USE  
 Domestic  Irrigation  Test  
 Municipal/Industrial  Monitor  Stock

5. WELL TYPE  
 Cable  Rotary  RVC  
 Air  Other \_\_\_\_\_

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Top Soil		0	2	
Pink Brn Black Rock		2	15	
Pink Brn Black Rock		20	44	
Pink Brn Black Rock		44	64	
Pink Brn Black Rock		64	124	
Pink Brn Black Rock		124	164	
Pink Brn Black Rock	Dgn	164	244	
Pink Brn Black Rock	Dgn	244	364	
Pink Brn Black Rock		364	424	
Pink Rock matrix +		424	444	
Pink Rock matrix		444	464	
Mixed Color Rock		464	474	
Brown Rock		474	484	
Brown Rock Basalt		484	494	
Brown Rock Basalt		494	504	
Brown/Green Rock matrix +		504	524	
Brown/Green Rock		524	534	
Light Green mixed Rock		534	565	

8. WELL CONSTRUCTION  
Depth Drilled 565 Feet Depth Cased 565 Feet

HOLE DIAMETER (BIT SIZE)

Inches	From	To	Feet	Feet
10	0	57		
8	57	565		

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
6 3/8	13	1.88	41	285
6 5/8	17	2.50	285	505
6 7/8	13	1.88	505	545
6 7/8	17	2.50	545	565

Perforation: mill 510T single row  
Size perforation: 1.090 x 3

From 505 feet to 545 feet  
From \_\_\_\_\_ feet to \_\_\_\_\_ feet  
From \_\_\_\_\_ feet to \_\_\_\_\_ feet  
From \_\_\_\_\_ feet to \_\_\_\_\_ feet

Surface Seal:  Yes  No Seal Type:  Neat Cement  
Depth of Seal 57  Cement Grout  
Placement Method:  Pumped  Concrete Grout  
 Poured

Gravel Packed:  Yes  No  
From \_\_\_\_\_ feet to \_\_\_\_\_ feet

Latitude: 4144.512N  
Longitude: 11922.342W  
NAD83

4174/973° N  
119.37/330° W  
NAD 27 (TA)

9. WATER LEVEL  
Static water level 2.6 feet below land surface  
Artesian flow \_\_\_\_\_ G.P.M. \_\_\_\_\_ P.S.I.  
Water temperature cold °F Quality Good

Date started 10/28 2009  
Date completed 10/31 2009

10. DRILLER'S CERTIFICATION  
This well was drilled under my supervision and the report is true to the best of my knowledge.  
Name Steve's pumps & well drilling Contractor  
Address 711-715 seals Rd Contractor  
JANESVILLE CA 96114  
Nevada contractor's license number issued by the State Contractor's Board 0071285  
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 2369  
Signed [Signature]  
By driller performing actual drilling on site or contractor  
Date 11/1/09

7. WELL TEST DATA

TEST METHOD:  Bailer  Pump  Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
30	1.0	1.0
100	1.0	1.0