

PRINT OR TYPE ONLY
 DO NOT WRITE ON BACK

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 62458

1. OWNER U.P.R.R. ADDRESS AT WELL LOCATION 300 Regan Pl. Fallon, NV
 MAILING ADDRESS 1400 DOUGLAS ST OMAHA, NE 68179
 2. LOCATION 1/4 SW 25 T 19 N R 28 E Churchill County
 PERMIT NO. _____ Issued by Water Resources Parcel No. _____ Subdivision Name _____

3. WORK PERFORMED
 New Well Replace Recondition Deepen Abandon Other Catholic Protection
 4. PROPOSED USE
 Domestic Irrigation Test Monitor Stock Municipal/Industrial
 5. WELL TYPE
 Cable Rotary RVC Air Other _____

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Lt Brown silty sand		0	20	20
Lt Brown silty clay		20	25	5
Lt Brown sand		25	35	10
Dr Brown silty clay		35	65	30
Black clay		65	75	10
Lt Brown sand		75	80	5
Lt Brown sandy clay		80	85	5
Lt Brown coarse sand		85	115	30
Brown clay		115	125	10
Grey clay		125	145	20
Black clay		145	155	10
Brown coarse sand		155	163	8
Grey silty clay		163	167	4
Grey silty clay w/sand gravel		167	175	8
Black white sand/gravel		175	197	22
Lt Brown sandy clay		197	225	28
Brown sand/gravel		225	240	15
Brown/white gravel		240	247	7
Lt Brown silty sand		247	257	10
Blue silty clay		257	265	8
Lt Brown silty clay		265	275	10
Brown/white sand/gravel		275	280	5
White clay		280	290	10
Lt Brown sandy clay		290	295	5
Lt Brown clay w/sand/gravel		295	305	10
N 39° 28.717' 39.478699° N				
W 118° 47.709' 118.794164° W				
WGS 84 NAD 27 (T4)				

8. WELL CONSTRUCTION
 Depth Drilled 305 Feet Depth Cased 304 Feet
 HOLE DIAMETER (BIT SIZE)
 From 10 Inches To 305 Feet
 From 0 Feet To 305 Feet
 From _____ Inches To _____ Feet
 From _____ Inches To _____ Feet
 CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
2"		.308	0	304

Perforations:
 Type perforation Drilled
 Size perforation 1/8 INCH
 From 179 feet to 304 feet
 From _____ feet to _____ feet
 Surface Seal: Yes No Seal Type:
 Neat Cement Cement Grout Concrete Grout
 Depth of Seal 160
 Placement Method: Pumped Poured
coke breeze
 Gravel Packed: Yes No
 From 160 feet to 304 feet

9. WATER LEVEL
 Static water level N/A feet below land surface
 Artesian flow N/A G.P.M. N/A P.S.I.
 Water temperature N/A °F Quality N/A

Date started 10/20/09, 2009
 Date completed 10/23, 2009

7. WELL TEST DATA

TEST METHOD: Bailer Pump Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)

2009 NOV 9 AM 11:37
 6-AON 6802

10. DRILLER'S CERTIFICATION
 This well was drilled under my supervision and the report is true to the best of my knowledge.
 Name Gregg Drilling & Testing Contractor
 Address 950 Howe Rd Martinez, CA 94553
 Nevada contractor's license number issued by the State Contractor's Board C23-0038113
 Nevada driller's license number issued by the Division of Water Resources, the on-site driller M-2322
 Signed Fui KH
 By driller performing actual drilling on site or contractor
 Date 10/24/09