STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S REPORT

OFFICE USE ONLY
Log No. 109313
Permit No.
Basin 070

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 64372

1. OWNER IDAHOAN FOODS / Colleen Iverson
MAILING ADDRESS 1 POTATO RD.
WINNEMUCCA, NV. 89445

ADDRESS AT WELL LOCATION 1 POTATO RD.
WINNEMUCCA, NV.
Subdivision Name: County: HUMBOLDT

2. LOCATION NE ¼ SW ¼ Sec 1 T 35N N/S R 37 E
PERMIT/WAIVER No. NEV89012 (issued by Water Resources) 010-355-16 Parcel No.

Latitude 40.934866
Longitude -117.768450
UTM E N
☐ NAD 27 ☑ NAD 83/WGS 84

3. WORKED PERFORMED
☒ New Well ☐ Replace ☐ Recondition ☐ Deepen ☐ Other

4. PROPOSED USE
☐ Domestic ☐ Irrigation ☐ Test ☐ Municipal/Industrial ☒ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☐ Rotary ☐ RVC ☐ Air ☒ Other AUGER

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
SILT	NO	0	18	18
FINE GRAIN SAND	NO	18	20	2
FINE GRAIN SILTY SAND	NO	20	38	18
SILT	NO	38	40	2
SANDY SILT (MOIST)	NO	40	47	7
SILT (MOIST)	NO	47	55	8
SILTS WITH SAND (MOIST)	NO	55	63	8
SAND WITH SOME SILT (WET)	YES	63	75	12

40.934963° N
117.767486° W
NAD 27 (TB)

Date started: 21-Oct, 20 09
Date completed: 21-Oct, 20 09

9. WELL CONSTRUCTION
Depth Drilled 75 Feet Depth Cased 75 Feet

HOLE DIAMETER (BIT SIZE)

		From		To	
8	Inches	0	Feet	75	Feet
	Inches		Feet		Feet
	Inches		Feet		Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
2		SCH. 40	0	~~68~~ 75

Perforations:
Type of perforation FACTORY SLOT
Size of perforation .020
From 55 feet to 75 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Annular Seal: ☒ Yes ☐ No
☒ Neat Cement 0 to 10 ☒ Pumped ☐ Poured
☐ Cement Grout to ☐ Pumped ☐ Poured
☐ Concrete Grout to ☐ Pumped ☐ Poured
☐ ≥30% Bentonite Grout to ☐ Pumped ☐ Poured

Gravel Pack: ☒ Yes ☐ No 53 to 75 ☐ Pumped ☒ Poured
Type: 10/20 SILICA SAND
Bentonite Chips: ☒ Yes ☐ No 10 to 53 ☐ Pumped ☒ Poured
Type: 3/8 BENTONITE CHIPS

7. Water Level
Static water level: 57 feet below land surface
Artesian Flow: NO G.P.M. P.S.I.
Water Temperature: <85 °F
Quality:

8. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☐ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name HAZ TECH DRILLING, INC. (Contractor)
Address PO BOX 940 (Contractor)
MERIDIAN, ID. 83680
Nevada contractor's license number issued by the *State Contractor's Board* 0038018
Nevada driller's license number issued by the Division of Water Resources, the *on-site driller* M-2137
Signed (By driller performing actual drilling on site or contractor)
Date 11-12-09

STATE ENGINEER'S OFFICE 2009 DEC -3 AM 10:52

(Rev. 05-06)
USE ADDITIONAL SHEETS IF NECESSARY