

STATE OF NEVADA  
 DIVISION OF WATER RESOURCES  
**WELL DRILLER'S PLUGGING REPORT**

OFFICE USE ONLY  
 Log No. 10934  
 Permit No. \_\_\_\_\_  
 Basin φ 7 φ

PRINT OR TYPE ONLY  
 DO NOT WRITE ON BACK

Please complete this form in its entirety in  
 accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 63664

1 OWNER City of Winnemucca ADDRESS AT WELL LOCATION Across the street from 12.5 Bridge Street  
 MAILING ADDRESS 90 W 4th Street Winnemucca, NV 89445 Subdivision Name: \_\_\_\_\_ County: Humboldt  
 2 LOCATION SW ¼ SE ¼ Sec 19 T 36N N/S R 38 E Latitude N 40°58.594' UTM E  NAD 27  
 PERMIT/WAIVER No. 9966/R-625 Longitude W 117°44.421' N  NAD 83/WGS 84  
Issued by Water Resources Parcel No.

3 TYPE OF WELL  Domestic  Irrigation  Test  Municipal/Industrial  Monitor  Stock  
 Is this well being plugged because a replacement well was drilled? Yes  
 If yes, what is replacement well NOI? 56275  
 Is there an existing well log? Yes  
 If yes, what is NDWR well log #? 221

4 EXISTING WELL CONSTRUCTION  
 Depth Drilled 525 Feet Depth Cased 499 Feet

EXISTING CASING SCHEDULE				
Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
10			0	499

7 WELL PLUGGING PROCEDURE  
 Was well cleaned out to total depth?  yes  no  
 If well was not cleaned out to total depth, please explain why:  
Pump was cemented in place  
 Was the well contaminated?  yes  no  
 Was the casing pulled?  yes  no  
 Was the casing over drilled?  yes  no  
 If casing was left in place, please show where additional perforations were made:  
 Additional Perforations:

Existing Perforations:

Type of perforation	Size of perforation	From	feet to	feet

Type of perforator used:

From	feet to	feet	Number of perfs per linear foot

5 WATER LEVEL  
 Static water level \_\_\_\_\_ feet below land surface  
 Artesian flow 100 G.P.M. P.S.I.  
 Water temperature Cool °F Quality \_\_\_\_\_

8 WELL PLUGGING MATERIALS

From	feet to	feet	Material Used	<input checked="" type="checkbox"/> Pumped	<input type="checkbox"/> Poured
200	feet to	470	Gopher Grout	<input checked="" type="checkbox"/>	<input type="checkbox"/>
0	feet to	200	Neat Cement	<input checked="" type="checkbox"/>	<input type="checkbox"/>
	feet to			<input type="checkbox"/>	<input type="checkbox"/>
	feet to			<input type="checkbox"/>	<input type="checkbox"/>
	feet to			<input type="checkbox"/>	<input type="checkbox"/>
	feet to			<input type="checkbox"/>	<input type="checkbox"/>

6 Additional Notes or Comments  
This well was plugged per the conditions in the Waiver (R-625) we received

Neat Cement Fluid Weight 15 lbs/gal  
 Bentonite Grout 20 % bentonite  
 Date Started 9/26/2009  
 Date Completed 11/15/2009

40.976664° N  
117.739387° W  
N40 27 (76)

9 DRILLER'S CERTIFICATION  
 This well was plugged and abandoned under my supervision and the report is true to the best of my knowledge.  
 Name Hydro Resources Nevada Inc dba Humboldt Drilling & Pump Co  
 Contractor  
 Address 4975 W Winnemucca Blvd.  
 Contractor  
Winnemucca NV 89445  
 Nevada contractor's license number issued by the State Contractor's Board 56797  
 Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1713  
 Signed Cheryl Jaynes  
 By driller performing actual drilling on site or contractor  
 Date 11/30/2009