

STATE OF NEVADA  
DIVISION OF WATER RESOURCES  
**WELL DRILLER'S REPORT**

OFFICE USE ONLY

Log No. 109536  
Permit No. \_\_\_\_\_  
Basin PSI

PRINT OR TYPE ONLY  
DO NOT WRITE ON BACK

Please complete this form in its entirety in  
accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 61083

1. OWNER Newmont Mining Corp. ADDRESS AT WELL LOCATION Gold Quarry  
MAILING ADDRESS PO Box 669 Hole #SL-5  
NW Carlin, NV 89822 Subdivision Name: \_\_\_\_\_ County: Eureka

2. LOCATION NE 1/4 SE 1/4 Sec 6 T 33N N/S R 52 E Latitude 40.775065-N UTM E 570380  NAD 27  
PERMIT/WAIVER No. NEV88011 Longitude 116.166611-W N 4513904  NAD 83/WGS 84  
Issued by Water Resources Parcel No. NAD 27 88

3. WORKED PERFORMED  
 New Well  Replace  Recondition  
 Deepen  Other

4. PROPOSED USE  
 Domestic  Irrigation  Test  
 Municipal/Industrial  Monitor  Stock

5. WELL TYPE  
 Cable  Rotary  RVC  
 Air  Other

6. LITHOLOGIC LOG

| Material   | Water Strata | From | To  | Thick-ness |
|--|--------------|------|-----|------------|
| Carlin Formation   |              | 0    | 188 | 188        |
| Mudstone - Siltstone Clay  |              |      |     |            |
| Put casing in well. Place 14<br>sks #8 sand from bottom to<br>3' above screen. 3/8" hole plug<br>in hole to 53' 1.1 yard. Pour in<br>200 gal. cement slurry 21 sks.<br>Develop well through 1 3/4"<br>trimmie until clean.<br>Build monument |              |      |     |            |

9. WELL CONSTRUCTION

|               |     |      |             |     |      |
|---------------|-----|------|-------------|-----|------|
| Depth Drilled | 188 | Feet | Depth Cased | 187 | Feet |
|---------------|-----|------|-------------|-----|------|

HOLE DIAMETER (BIT SIZE)

|        | From | To  |
|--------|------|-----|
| 14 3/4 | 0    | 20  |
| 8 1/4  | 20   | 188 |

CASING SCHEDULE

| Size O.D.<br>(Inches) | Weight/Ft.<br>(Pounds) | Wall Thickness<br>(Inches) | From<br>(Feet) | To<br>(Feet) |
|-----------------------|------------------------|----------------------------|----------------|--------------|
| 4                     | PVC                    | 1/4                        | +3             | 187          |

Perforations:

| Type of perforation | Slot        |
|---------------------|-------------|
| Size of perforation | 0.02        |
| From 167            | feet to 187 |
| From                | feet to     |
| From                | feet to     |
| From                | feet to     |

Annular Seal:  Yes  No

Neat Cement 0 to 53  Pumped  Poured  
 Cement Grout to  Pumped  Poured  
 Concrete Grout to  Pumped  Poured  
 ≥30% Bentonite Grout to  Pumped  Poured

Gravel Pack:  Yes  No 188 to 164  Pumped  Poured  
 Type: #8 Sand

Bentonite Chips:  Yes  No 164 to 53  Pumped  Poured  
 Type: 3/8" Hole Plug Chips

7. Water Level

Static water level: 143 feet below land surface  
 Artesian Flow: No G.P.M. N/A P.S.I.  
 Water Temperature: Warm °F  
 Quality: Good

8. WELL TEST DATA

| TEST METHOD:  | G.P.M.   | Draw Down<br>(Feet Below Static) | Time (Hours) |
|---|----------|----------------------------------|--------------|
| <input type="checkbox"/> Bailer <input type="checkbox"/> Pump <input type="checkbox"/> Air Lift | <u>8</u> |                                  |              |

10. DRILLER'S CERTIFICATION

This well was drilled under my supervision and the report is true to the best of my knowledge.

Name Eklund Drilling Company, Inc.  
 Address PO Box 2748  
Elko, NV 89803  
 Nevada contractor's license number 0030823  
 issued by the State Contractor's Board  
 driller's license number issued by the 2089  
 Division of Water Resources, the on-site driller  
 Signed Donald Schoedel  
 By driller performing actual drilling on site or contractor  
 Date 3/18/2009

(Rev. 05-06)

USE ADDITIONAL SHEETS IF NECESSARY