STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S REPORT

OFFICE USE ONLY
Log No. 109539
Permit No.
Basin 087

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 65220

1. OWNER Kleinfelder
MAILING ADDRESS 4835 Longley Lane
Reno NV 89502

ADDRESS AT WELL LOCATION PSF-09-002
Larkin Circle
Subdivision Name: County: Washoe

2. LOCATION SE ¼ SE ¼ Sec 11 T 19 N S R 20 E
PERMIT/WAIVER No. MO 1558
Issued by Water Resources Parcel No.

Latitude 39.521114 N
Longitude 119.695660 W
NAD 27 (TA)

UTM E 268277.5 ☒ NAD 27
N 4377869.0 ☐ NAD 83/WGS 84

3. WORKED PERFORMED
☒ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Other

4. PROPOSED USE
☐ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☒ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☐ Rotary ☐ RVC
☐ Air ☒ Other Sonic

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
fill - sands		0	3	3
poorly graded sand		3	7	4
sandy clay		7	14	7
silty sand		14	17.5	3.5
poorly graded sand		17.5	27	9.5
clayey gravel		27	30	3
poorly graded sand		30	32	2
clayey gravel		32	35	3
poorly graded gravel		35	37	2
poorly graded gravel		37	42.5	5.5
poorly graded sand		42.5	44.5	2
clayey sand		44.5	46.5	2
sandy clay		46.5	50	3.5
clayey gravel		50	53.5	3.5
clayey sand		53.5	57	3.5
silty gravel (rock)		57	60	3

Date started: 11/13, 20 09
Date completed: 11/13, 20 09

7. Water Level
Static water level: 24.31 feet below land surface
Artesian Flow: G.P.M. P.S.I.
Water Temperature: °F
Quality:

8. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☐ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)

9. WELL CONSTRUCTION
Depth Drilled 60 Feet Depth Cased 40 Feet

HOLE DIAMETER (BIT SIZE)

		From		To	
6	Inches	0	Feet	60	Feet
	Inches		Feet		Feet
	Inches		Feet		Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
2		sch 80	0	40

Perforations:
Type of perforation Hor Slot
Size of perforation .020
From 40 feet to 5 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Annular Seal: ☒ Yes ☐ No

☐ Neat Cement	to		☐ Pumped	☒ Poured
☒ Cement Grout	60 to 41		☒ Pumped	☐ Poured
☐ Concrete Grout	to		☐ Pumped	☐ Poured
☐ ≥30% Bentonite Grout	to		☐ Pumped	☐ Poured

Gravel Pack: ☒ Yes ☐ No 41' to 3' ☐ Pumped ☒ Poured
Type:
Bentonite Chips: ☒ Yes ☐ No 3 to 1 ☐ Pumped ☒ Poured
Type: med chip

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name WDC
Contractor
Address PO Box 141
Contractor
Zamora Ca 95698
Nevada contractor's license number issued by the State Contractor's Board 0012852
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1880
Signed
By driller performing actual drilling on-site or contractor
Date 11/13/09

USE ADDITIONAL SHEETS IF NECESSARY

(Rev. 05-06)

(NSPO 3-08) (O) 627