STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S REPORT

OFFICE USE ONLY
Log No. 109581
Permit No.
Basin 179
AS-6
NOTICE OF INTENT NO. 62025

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

1. OWNER Chevron Env Management Co.
MAILING ADDRESS 6001 Bollinger Cnyn. Rd.
San Ramon, CA 94583

ADDRESS AT WELL LOCATION 801 East Aultman St.
Ely, NV 89301
Subdivision Name:
County: White Pine

2. LOCATION SE ¼ NW ¼ Sec 15 T 16 N S R 63 E
PERMIT/WAIVER No. 6-002034 (Issued by Water Resources) 002-054-09 (Parcel No.)

Latitude 39°15.250'
Longitude 114°57.331'
UTM E
N
☐ NAD 27
☒ NAD 83/WGS 84

3. WORKED PERFORMED
☒ New Well ☐ Replace ☐ Recondition ☐ Deepen ☐ Other

4. PROPOSED USE
☐ Domestic ☐ Irrigation ☐ Test ☐ Municipal/Industrial ☒ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☐ Rotary ☐ RVC ☐ Air ☒ Other Single

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Fill Material				
sand, silt, cobble		0	6	6
Sandy silt, cobble grey		6	80	74
Clay		80	82	2
WATER	X			
39.254227° N				
114.871332° W				
NAD 27 TR				

Date started: 1-18, 20 09
Date completed: 1-18, 20 09

9. WELL CONSTRUCTION
Depth Drilled 82 Feet Depth Cased 80 Feet

HOLE DIAMETER (BIT SIZE)

		From		To	
6	Inches	0	Feet	82	Feet
	Inches		Feet		Feet
	Inches		Feet		Feet

CASING SCHEDULE

Size O.D. (inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
2		Sched 40 PVC	0	80

Perforations:
Type of perforation PVC Screen
Size of perforation .020
From 79.5 feet to 52 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Annular Seal: ☒ Yes ☐ No
☒ Neat Cement 0 to 74 ☒ Pumped ☐ Poured
☐ Cement Grout to ☐ Pumped ☐ Poured
☐ Concrete Grout to ☐ Pumped ☐ Poured
☐ ≥30% Bentonite Grout to ☐ Pumped ☐ Poured

Gravel Pack: ☒ Yes ☐ No 77 to 82 ☐ Pumped ☒ Poured
Type: Monterey #3
Bentonite Chips: ☒ Yes ☐ No 74 to 77 ☐ Pumped ☒ Poured
Type: 3/8" Hole Plug Chips

7. Water Level
Static water level: 73 feet below land surface
Artesian Flow: G.P.M. P.S.I.
Water Temperature: °F
Quality:

8. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☐ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name (Contractor) Bobart Longyear
Address (Contractor) 3894 Railroad Avenue
Yuba City, CA 95991
Nevada contractor's license number issued by the State Contractor's Board 0021976
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 2234
Signed (By driller performing actual drilling on-site or contractor)
Date 2-5-09

(Rev. 05-06)

USE ADDITIONAL SHEETS IF NECESSARY

(NSPO 3-08) (O) 627