

STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S REPORT

OFFICE USE ONLY
Log No. 1091625
Permit No. _____
Basin 044

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 62058

1. OWNER Carefree Homes
MAILING ADDRESS 3260 South Redwood
Salt Lake City, Ut 84119

ADDRESS AT WELL LOCATION 6380 Filmore
Subdivision Name: _____ County: Elko

2. LOCATION NW 1/4 SE 1/4 Sec 31 T 36N N/S R 57 E
PERMIT/WAIVER No. 012-013-003
Issued by Water Resources Parcel No.

Latitude 40.57.675N UTM E NAD 27
Longitude 115.35.557W N NAD 83/WGS 84

3. WORKED PERFORMED
 New Well Replace Recondition
 Deepen Other

4. PROPOSED USE
 Domestic Irrigation Test
 Municipal/Industrial Monitor Stock

5. WELL TYPE
 Cable Rotary RVC
 Air Other MUD

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thick-ness
Sandy Loam		0	3	3
Sand & Gravel		3	38	35
Hard Pan		38	42	4
Sand & Gravel		42	68	26
Clay		68	99	31
Sand & Gravel	X	99	104	5
Sand & Clay Mixed		104	112	8
Sand & Gravel	X	112	129	17
Clay		129	150	21
Sand & Gravel	X	150	180	30

Handwritten: 46.961330° N, 115.591218° W, NAD 27 (2)

Vertical Stamp: RECEIVED 2010 JUL -2 AM 11:41 STATE ENGINEERS OFFICE

9. WELL CONSTRUCTION

Depth Drilled 180 Feet Depth Cased 180 Feet

HOLE DIAMETER (BIT SIZE)

	From	To
10 5/8 Inches	0	180
Inches		
Inches		

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
6	12.92	188	+1	20
6		SDR-17	20	180

Perforations:

Type of perforation Screen
Size of perforation 0.032

From	to
160	180

Annular Seal: Yes No

Material	to	Method
Neat Cement		<input type="checkbox"/> Pumped <input type="checkbox"/> Poured
Cement Grout		<input type="checkbox"/> Pumped <input type="checkbox"/> Poured
<input checked="" type="checkbox"/> Concrete Grout	0 to 19	<input type="checkbox"/> Pumped <input checked="" type="checkbox"/> Poured
<input type="checkbox"/> ≥30% Bentonite Grout		<input type="checkbox"/> Pumped <input type="checkbox"/> Poured

Gravel Pack: Yes No 51 to 180 Pumped Poured
Type: 3/8 pea gravel

Bentonite Chips: Yes No 19 to 51 Pumped Poured
Type: 3/8 Kwik Plugg

7. Water Level
Static water level: 65 feet below land surface
Artesian Flow: _____ G.P.M. _____ P.S.I.
Water Temperature: cold °F
Quality: _____

8. WELL TEST DATA

TEST METHOD: Bailor Pump Air Lift

	G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
Approx	20		6.8

10. DRILLER'S CERTIFICATION

This well was drilled under my supervision and the report is true to the best of my knowledge.

Name Sharel c. Fertig Sr dba Fertig Drilling Company
Contractor

Address P.O. Box 525
Contractor

Elko, NV 89801

Nevada contractor's license number issued by the State Contractor's Board 031904

Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1584

Signed Sharel Fertig
By driller performing actual drilling on site or contractor

Date 6-30-08

(Rev. 05/90)

USE ADDITIONAL SHEETS IF NECESSARY