WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

Plugging

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 109652
Permit No.
Basin 031

NOTICE OF INTENT NO. 63080

1. OWNER Nevada Geothermal Power
MAILING ADDRESS 657 Anderson St.
Winnemucca NV. 89445

ADDRESS AT WELL LOCATION Jungo Rd.
Winnemucca NV.

2. LOCATION SW ¼ NW ¼ Sec. 35 T. 36 N/S R. 34 E. Humboldt County
PERMIT NO. W-630 A/77056 (Issued by Water Resources) ~~72056~~ (Parcel No.) 5-34/-36 (Subdivision Name)

3. WORK PERFORMED
■ New Well ☐ Replace ☐ Recondition
☐ Deepen ■ Abandon ☐ Other

4. PROPOSED USE
☐ Domestic ☐ Irrigation ■ Test
☐ Municipal/Industrial ☐ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☐ Rotary ■ RVC
☐ Air ☐ Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Topsoil	0	0	5	5
Sand	0	5	40	35
Sand, Gravel	80	40	120	80
Sand, Gravel, Brown Clay		120	160	40
Sand, Gravel, little clay		160	180	20
Sand, Gravel		180	220	40
Sand, Gravel, Red silt		220	260	40
Sand, Red silt		260	300	40

Drilled hole to depth obtained water sample plugged hole per state regs.

Plugged 0 to 50 Cement
50 to 100 Hole plug
100 to 300 Abandon with slurry

GPS N 40.953191
W 118.137576
NAD 27 (A)

Date started 8.21, 2008
Date completed 8.21, 2008

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ■ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
20		.25

8. WELL CONSTRUCTION
Depth Drilled 300 Feet Depth Cased N/A Feet

HOLE DIAMETER (BIT SIZE)

	From	To
6 ■ Inches	0 Feet	300 Feet
Inches	Feet	Feet
Inches	Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
	NA			

Perforations:
Type perforation NA
Size perforation
From feet to feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ■ Yes ☐ No
Depth of Seal 50
Placement Method: ■ Pumped ☐ Poured
Seal Type: ■ Neat Cement ☐ Cement Grout ☐ Concrete Grout

Gravel Packed: ☐ Yes ■ No
From feet to feet

9. WATER LEVEL
Static water level 80 feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature Cool °F Quality Clear

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name Firstgold Corp. (Contractor)
Address P.O. Box 6 (Contractor)
Lovelock NV.
Nevada contractor's license number issued by the State Contractor's Board 0071020
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 2032
Signed Harold Morris (By driller performing actual drilling on site or contractor)
Date 9-24-08

(Rev. 12-01) USE ADDITIONAL SHEETS IF NECESSARY (O)-627