

3 MW-1

STATE OF NEVADA  
DIVISION OF WATER RESOURCES  
WELL DRILLER'S PLUGGING REPORT

OFFICE USE ONLY  
Log No. 109839  
Permit No. 666  
Basin

PRINT OR TYPE ONLY  
DO NOT WRITE ON BACK

Please complete this form in its entirety in  
accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 65400

1 OWNER BARRIK TRSV  
MAILING ADDRESS HC 66 BOX 200  
GOLEONDA NV 89414

ADDRESS AT WELL LOCATION HC 66 BOX 200  
28 MI NE OF GOLEONDA NV 89414  
Subdivision Name: \_\_\_\_\_ County: Numbolt

2 LOCATION NE 1/4 NW 1/4 Sec 3 T 38 S R 49 E  
PERMIT/WAIVER No. \_\_\_\_\_  
Issued by Water Resources \_\_\_\_\_ Parcel No. \_\_\_\_\_

Latitude 41° 12' 23.06" N UTM E \_\_\_\_\_  NAD 27  
Longitude 117° 13' 55.98" W N \_\_\_\_\_  NAD 83/WGS 84  
41.206906° N; 117.232217° W K802310

3 TYPE OF WELL  
 Domestic  Irrigation  Test  
 Municipal/Industrial  Monitor  Stock

Is this well being plugged because a replacement well was drilled? YES  
If yes, what is replacement well NOI? 33275

Is there an existing well log? NO  
UNABLE TO LOCATE.  
If yes, what is NDWR well log #?

4 EXISTING WELL CONSTRUCTION  
Depth Drilled 127 Feet Depth Cased 127 Feet

7 WELL PLUGGING PROCEDURE  
Was well cleaned out to total depth?  yes  no  
If well was not cleaned out to total depth, please explain why:

Size O.D. (Inches)	Weight/Ft (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
<u>4.5</u>	<u>PVC</u>	<u>SCH 40</u>	<u>0</u>	<u>127</u>

Was the well contaminated?  yes  no  
Was the casing pulled?  yes  no  
Was the casing over drilled?  yes  no  
If casing was left in place, please show where additional perforations were made:  
Additional Perforations:  
Type of perforator used:  
From \_\_\_\_\_ feet to \_\_\_\_\_ feet Number of perfs per linear foot \_\_\_\_\_  
From \_\_\_\_\_ feet to \_\_\_\_\_ feet Number of perfs per linear foot \_\_\_\_\_  
From \_\_\_\_\_ feet to \_\_\_\_\_ feet Number of perfs per linear foot \_\_\_\_\_  
From \_\_\_\_\_ feet to \_\_\_\_\_ feet Number of perfs per linear foot \_\_\_\_\_  
From \_\_\_\_\_ feet to \_\_\_\_\_ feet Number of perfs per linear foot \_\_\_\_\_  
From \_\_\_\_\_ feet to \_\_\_\_\_ feet Number of perfs per linear foot \_\_\_\_\_

Existing Perforations:  
Type of perforation UNKNOWN  
Size of perforation \_\_\_\_\_  
From \_\_\_\_\_ feet to \_\_\_\_\_ feet  
From \_\_\_\_\_ feet to \_\_\_\_\_ feet

5 WATER LEVEL  
Static water level DRY feet below land surface  
Artesian flow \_\_\_\_\_ G.P.M. \_\_\_\_\_ P.S.I.  
Water temperature \_\_\_\_\_ °F Quality \_\_\_\_\_

8 WELL PLUGGING MATERIALS  
Material Used  
From 20 feet to 127 feet BENTONITE GR.  Pumped  Poured  
From 0 feet to 20 feet CEMENT  Pumped  Poured  
From \_\_\_\_\_ feet to \_\_\_\_\_ feet \_\_\_\_\_  Pumped  Poured  
From \_\_\_\_\_ feet to \_\_\_\_\_ feet \_\_\_\_\_  Pumped  Poured  
From \_\_\_\_\_ feet to \_\_\_\_\_ feet \_\_\_\_\_  Pumped  Poured  
From \_\_\_\_\_ feet to \_\_\_\_\_ feet \_\_\_\_\_  Pumped  Poured

6 Additional Notes or Comments  
\* TAG DEPTH OF WELL AT  
127 FT. UNABLE TO PULL PVC  
CASINGS. INSTALL TREMI  
PIPE. PUMP BENTONITE  
GROUT FROM BOTTOM TO  
20 FT. CEMENT TOP 20 FT.  
BROKE PVC CASING OFF 2 FT  
BELOW GROUND SURFACE.  
REMOVE 5 FT STEEL CASING.  
BACKFILL TOP 1 FT. WITH DIRT.  
\* THIS WAS A DRY WELL.

Neat Cement Fluid Weight \_\_\_\_\_ lbs/gal  
Bentonite Grout 12.5 % bentonite  
Date Started 11-16-09  
Date Completed 11-16-09

9 DRILLER'S CERTIFICATION  
This well was plugged and abandoned under my supervision and the report is true to the best of my knowledge.  
Name LAYNE CHRISTENSEN CO. Contractor  
Address 12030 E. RIGGS RD. Contractor  
CHANDLER, AZ 85249  
Nevada contractor's license number 43608  
issued by the State Contractor's Board  
Nevada driller's license number issued by the M-2215  
Division of Water Resources, the on-site driller  
Signed Rodney Michael  
By driller performing actual drilling on site or contractor  
Date 12/30/09