

Log No. _____
 Permit No. _____
 Basin **629**

PRINT OR TYPE ONLY
 DO NOT WRITE ON BACK

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. **50427**

1. OWNER The Boeing Company ADDRESS AT WELL LOCATION Rocketdyne, NV Field Laboratory, Washoe County, Nevada
 MAILING ADDRESS 6633 Canoga Avenue D-393T-487 2200 Whiskey Springs Road, Reno, Nevada
Canoga Park, CA 91303
 2. LOCATION SW 1/4 SW 1/4 Sec 12 T 22N N/S R 21 E Washoe County
 PERMIT NO. DEX-16 R-422 077-110-22 Area D Palomino Valley Subdivision Name

3. WORK PERFORMED
 New Well Replace Recondition
 Deepen Abandon Other.....
 4. PROPOSED USE
 Domestic Irrigation Test
 Municipal/Industrial Monitor Stock
 5. WELL TYPE
 Cable Rotary PVC
 Air Other: **TUBEX**

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thick-ness
Sand with gravel, light brown, fine to coarse sand fine and coarse gravel, subangular some silt, well graded dry to slightly moist		0	30	30
Silty sand with gravel light brown, fine to coarse sand fine and coarse gravel subangular, saturated from drilling water, well graded.		30	67	37
Silty sand with clay, red brown weathered bed rock		67	69	2
Tuff of Chimney Springs red brown, moderately welded, abundant smoky quartz bipyramids		67	73.2	6.2

8. WELL CONSTRUCTION
 Depth Drilled 73.2 Feet Depth Cased 69 Feet
 HOLE DIAMETER (BIT SIZE)
 From 0 Feet To 73.2 Feet
 11.5 Inches _____ Feet _____ Feet
 _____ Inches _____ Feet _____ Feet
 _____ Inches _____ Feet _____ Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
6	Sch 80	PVC Casing	0	69

End cap at 69 ft. Stainless steel centralizers
 Locking monument

Perforations:
 Type perforation factory sawed slot
 Size perforation 0.020" slots
 From 34 feet to 69 feet
 From _____ feet to _____ feet

Surface Seal: Yes No Seal Type:
 Depth of Seal 27.5 Neat Cement
 Placement Method: Pumped Cement Grout
 Poured Concrete Grout
 Bentonite seal: 27.5-29.1
 Gravel Packed: Yes No SRI#8
 From 29.1 feet to 73.2 feet

9. WATER LEVEL
 Static water level 42.1 feet below land surface
 Artesian flow Not known G.P.M. _____ P.S.I. _____
 Water temperature cold °F Quality not known

Date started November 6, 2002, 20____
 Date completed November 8, 2002, 20____

7. WELL TEST DATA

TEST METHOD:	TEST METHOD: <input type="checkbox"/> Bailer <input type="checkbox"/> Pump <input type="checkbox"/> Air Lift		
	G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
No test			
Information received <u>12-04-06</u>			

10. DRILLER'S CERTIFICATION
 This well was drilled under my supervision and the report is true to the best of my knowledge.
 Name WAYNE DRILLING, INC. Contractor
 Address P.O. BOX 12370 Contractor
RENO, NEVADA 89510
 Nevada contractor's license number issued by the State Contractor's Board 0022549
 Nevada driller's license number issued by the Division of Water Resources, the on-site driller 908
 Signed [Signature] by driller performing actual drilling on site or contractor
 Date December 4, 2006