

Log No. _____
 Permit No. _____
 Basin 484

PRINT OR TYPE ONLY
 DO NOT WRITE ON BACK

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 48424

1. OWNER THE BOEING COMPANY ADDRESS AT WELL LOCATION Rocketdyne NV Field
 MAILING ADDRESS 6633 Canoga Avenue D-393 T-484 Laboratory, Washoe County, Nevada
Canoga Park, CA 91303 800 Axe Handle Canyon Road, Reno, Nevada 89510

2. LOCATION NE 1/4 SW 1/4 Sec 28 T 22N N/S R 21 E Washoe County
 PERMIT NO. Affir. 6-30-03 B-22A 076-150-01 Area B Palomino Valley
Issued by Water Resources Parcel No. Subdivision Name

3. WORK PERFORMED
 New Well Replace Recondition
 Deepen Abandon Other _____

4. PROPOSED USE
 Domestic Irrigation Test
 Municipal/Industrial Monitor Stock

5. WELL TYPE
 Cable Rotary RVC
 Air Other _____

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thick-ness
FILL/ALLUVIUM				
coarse sand, granitic, angular, well graded, slightly moist, pale yellowish brown		0	10	10
GRANDODIORITE				
medium granied, slightly weathered, pale yellowish brown		10	59	49
slightly weathered, light brownish grey		@20		
multiple fractures		25	30	5
borehole making water	X	@35		
borehole making approx 15 GPM	X			
weathered fracture		54	56	2
Total depth of well		59	feet	

8. WELL CONSTRUCTION
 Depth Drilled 59 Feet Depth Cased 58.8 Feet

HOLE DIAMETER (BIT SIZE)
 From 9 Inches To 0 Feet 59 Feet
 _____ Inches _____ Feet _____ Feet
 _____ Inches _____ Feet _____ Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
4"	Sch 40	PVC casing	0	58.8
4" end cap.	4"	stainless steel centralizers		
@16 ft. Well seal at top				

Perforations:
 Type perforation factory sawed slot
 Size perforation 0.020 slot
 From 13.3 feet to 58.8 feet
 From _____ feet to _____ feet

Surface Seal: Yes No Seal Type:
 Depth of Seal 9.4 ft. Neat Cement
 Cement Grout
 Concrete Grout

Placement Method: Pumped Poured
 Bentonite seal: 9.4-11 ft
 Gravel Packed: Yes No SRI #8 sand
 From 11 feet to 59 feet

9. WATER LEVEL
 Static water level 18.8 feet below land surface
 Artesian flow _____ G.P.M. _____ P.S.I.
 Water temperature cold °F Quality not known

Date started July 7, 2003, 20
 Date completed July 8, 2003, 20

7. WELL TEST DATA

TEST METHOD:	G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
<input type="checkbox"/> Bailer <input type="checkbox"/> Pump <input checked="" type="checkbox"/> Air Lift	<u>15</u>		
Information recieved	<u>12-04-06</u>		

10. DRILLER'S CERTIFICATION
 This well was drilled under my supervision and the report is true to the best of my knowledge.
 Name WAYNE DRILLING, INC. Contractor
 Address P.O. BOX 12370 Contractor
RENO, NEVADA 89510
 Nevada contractor's license number 0022549
 issued by the State Contractor's Board
 Nevada driller's license number issued by the 908
 Division of Water Resources, the on-site driller
 Signed [Signature]
 By driller performing actual drilling on site or contractor
 Date December 4, 2006