

Log No. _____
 Permit No. 689
 Basin _____

PRINT OR TYPE ONLY
 DO NOT WRITE ON BACK

WELL DRILLER'S REPORT

Please complete this form in its entirety in
 accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 50439

1. OWNER THE BOEING COMPANY ADDRESS AT WELL LOCATION Rocketdyne, NV Field
6633 Canoga Avenue D-393 T-487 Laboratory, Washoe County, Nevada
 MAILING ADDRESS Canoga Park, CA 91303 800 Axe Handle Canyon Road, Reno, Nevada 89510

2. LOCATION NE 1/4 SW 1/4 Sec. 28 T. 22N N/S R. 21 E Washoe County
 PERMIT NO. Affid. 3-25-03/B-20A 076-150-01 Area B Palomino Valley
Issued by Water Resources Parcel No. Subdivision Name

3. WORK PERFORMED
 New Well Replace Recondition
 Deepen Abandon Other _____

4. PROPOSED USE
 Domestic Irrigation Test
 Municipal/Industrial Monitor Stock

5. WELL TYPE
 Cable Rotary RVC
 Air Other TUBEX

6. LITHOLOGIC LOG

| Material | Water Strata | From | To | Thick-ness |
|---|--------------|------|------|------------|
| GRANODIORITE | | 0 | 47.2 | 47.2 |
| slightly to moderately weathered | | 0 | 2 | |
| fresh material medium dark grey, fine to medium grained, abundant biotite | | | | |
| slightly weathered soft, weathered fracture zone | | @5 | 15 | 2 |
| fracture | | @21 | | |
| soft fracture | | 26 | 27 | 1 |
| very hard fracture making approx 5 GPM | | 27 | 32 | 5 |
| fracture | | 41 | 42 | 1 |
| Total depth of borehole | | 47.2 | | |

8. WELL CONSTRUCTION
 Depth Drilled 47.2 Feet Depth Cased 46.7 Feet

HOLE DIAMETER (BIT SIZE)
 From To
9 Inches 0 Feet 47.2 Feet
 _____ Inches _____ Feet _____ Feet
 _____ Inches _____ Feet _____ Feet

CASING SCHEDULE

| Size O.D. (Inches) | Weight/Ft. (Pounds) | Wall Thickness (Inches) | From (Feet) | To (Feet) |
|--------------------|---------------------|---|-------------|-----------|
| 4 | Sch 40 | PVC casing | 0 | 46.7 |
| 4" end | cap. 4" | security cap. 4" stainless steel centralizers | | |
| | | 8" locking monument | | |

Perforations: @21'
 Type perforation factory sawed slot
 Size perforation 0.020" slots
 From 16.7 feet to 46.7 feet
 From _____ feet to _____ feet

Surface Seal: Yes No Seal Type:
 Depth of Seal 10.4 ft Neat Cement
 Cement Grout
 Placement Method: Pumped Poured Concrete Grout
 Bentonite seal: 10.4-12.9 ft
 Gravel Packed: Yes No SRI#8 sand
 From 12.9 feet to 47.2 feet

9. WATER LEVEL
 Static water level 11.6 feet below land surface
 Artesian flow _____ G.P.M. _____ P.S.I.
 Water temperature cold °F Quality not known

Date started April 14, 2003, 20_____
 Date completed April 15, 2003, 20_____
 7. WELL TEST DATA

TEST METHOD: Bailer Pump Air Lift

| | G.P.M. | Draw Down (Feet Below Static) | Time (Hours) |
|-------------------------------|--------|-------------------------------|--------------|
| No test | | | |
| | | | |
| | | | |
| | | | |
| Information received 12-04-06 | | | |

10. DRILLER'S CERTIFICATION
 This well was drilled under my supervision and the report is true to the best of my knowledge.
 Name WAYNE DRILLING, INC. Contractor
 Address P.O. BOX 12370 Contractor
RENO, NEVADA 89510
 Nevada contractor's license number 0022549
 issued by the State Contractor's Board
 Nevada driller's license number issued by the 908
 Division of Water Resources, the on-site driller
 Signed [Signature]
 By driller performing actual drilling on site or contractor
 Date December 4, 2006