WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 109927
Permit No.
Basin 084

NOTICE OF INTENT NO. 37000

1. ~~OWNER~~ Consultant: SRK Consulting Engineers & Scientists
MAILING ADDRESS 5250 Neil Road, Suite 300
Reno, Nevada 89502

Client:
ADDRESS AT WELL LOCATION Rocketdyne Former Field La
Axe Handle Canyon Road
Spanish Springs, Nevada

2. LOCATION NW ¼ SW ¼ Sec. 28 T 22N N/S R 21 E Washoe County
PERMIT NO. Well B-19A (Issued by Water Resources) 76-150-01 (Parcel No.) Area B (Subdivision Name)

3. WORK PERFORMED
☒ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Abandon ☐ Other

4. PROPOSED USE
☐ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☒ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☒ Rotary ☐ RVC
☒ Air ☐ Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Silty sand, yellowihs brown, loose to dense, moist,fine to medium grained		0	3	3
Granodorite, fine to medium grained, with feltspar, quartz & biotite graines		3	180	173
Andesite		180	208	28
Granodiorite same as above		208	274	66

Date started 10-25-99, 20
Date complated 10-29-99, 20

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☐ Air Lift

	G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
No test			

8. WELL CONSTRUCTION
Depth Drilled 274 Feet Depth Cased 272 Feet

HOLE DIAMETER (BIT SIZE)

		From	To
12¼ Inches		0 Feet	29 Feet
9 Inches		29 Feet	274 Feet
Inches		Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
10 Temporary		- pull back	0	29
5"OD		.188	29	272
Welded end cap, centralizers, 8"x5' monument				

Perforations:
Type perforation factory double row sawed slot
Size perforation 3/32 x 2½
From 215 feet to 272 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☒ Yes ☐ No
Depth of Seal 0-205 feet & 0-29' 10"
Placement Method: ☒ Pumped ☐ Poured
Bentonite seal: 205-210'
Gravel Packed: ☒ Yes ☐ No
From 210-211½ SRI#30 sand 211½-274 feet to feet

Seal Type:
☒ Neat Cement
☐ Cement Grout
☐ Concrete Grout
Lonestar Coarse Aquarium

9. WATER LEVEL
Static water level 215 feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature °F Quality not known

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name Wayne Drilling, Inc. (Contractor)
Address P.O. Box 12370 (Contractor)
Reno, Nevada 89510
Nevada contractor's license number issued by the State Contractor's Board 0022549
Nevada driller's license number issued by the Division of Water Resources, the on site driller 908
Signed [signature] (By driller performing actual drilling on site or contractor)
Date February 2, 2000

(Rev. 12-01) USE ADDITIONAL SHEETS IF NECESSARY (O)-627