

PRINT OR TYPE ONLY
 DO NOT WRITE ON BACK

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 37862

1. Consultant: CDM Engineers & Constructors, Inc. Client: Santa Fe Pipeline
 OWNER: ADDRESS AT WELL LOCATION: Vista Canyon Group Sparks Solvent/Fuel Site
 MAILING ADDRESS: 7025 Longley Lane, Suite #20 Reno, Nevada 89511 Sparks, Nevada
 2. LOCATION: NE 1/4 NE 1/4 Sec. 9 T. 19N N/S R. 20 E. Washoe County
 PERMIT NO. Performance MW 1 034-102-13 Sparks Solvent/Fuel Site
Issued by Water Resources Parcel No. Subdivision Name

3. WORK PERFORMED
 New Well Replace Recondition
 Deepen Abandon Other.....
 4. PROPOSED USE
 Domestic Irrigation Test
 Municipal/Industrial Monitor Stock
 5. WELL TYPE
 Cable Rotary RVC
 Air Other TUBEX

6. LITHOLOGIC LOG

| Material | Water Strata | From | To | Thick-ness |
|--|--------------|------|----|------------|
| Fill, clayey sands, medium brown, moist, rootlets | | 0 | 15 | 15 |
| Gravel-Sand mix, greyish brown, saturated, cobbles, fine to coarse gravels, medium to coarse sands, rounded to subangular well graded, silt lenses | | 15 | 39 | 24 |
| Gravel-Sand mix, dark greyish brown, saturated, cobbles, fine to coarse gravels, medium to coarse sands, rounded to subangular, well graded, silt lenses | | 39 | 41 | 2 |

8. WELL CONSTRUCTION
 Depth Drilled 41 Feet Depth Cased 39 1/2 Feet
 HOLE DIAMETER (BIT SIZE)
 From 6 Inches To 0 Feet 41 Feet
 Inches Feet Feet
 Inches Feet Feet

CASING SCHEDULE

| Size O.D. (Inches) | Weight/Ft. (Pounds) | Wall Thickness (Inches) | From (Feet) | To (Feet) |
|--------------------|---------------------|-------------------------|-------------|-----------|
| 2" PVC | | sch 40 | 0 | 19 1/2 |
| 2" PVC | Box end | cap, 2" PVC | Locking cap | |
| 6"x5' | Steel | monument | | |

Perforations: Factory sawed slot
 Type perforation
 Size perforation :060
 From 19 1/2 feet to 39 1/2 feet
 From feet to feet
 From feet to feet
 From feet to feet
 From feet to feet

Surface Seal: Yes No Seal Type:
 Depth of Seal 0-16 Neat Cement
 Placement Method: Pumped Cement Grout
 Poured Concrete Grout
 Bentonite seal 3/8 coated pellets 16-18 feet
 Gravel Packed: Yes No
 From 18-41 ft. Filter pack #6 Corase Aquarium

9. WATER LEVEL
 Static water level 10 feet below land surface
 Artesian flow G.P.M. P.S.I.
 Water temperature °F Quality not known

Date started January 19, 1999, 19.....
 Date completed January 19, 1999, 19.....

7. WELL TEST DATA

| TEST METHOD: | G.P.M. | Draw Down (Feet Below Static) | Time (Hours) |
|---|--------|-------------------------------|--------------|
| <input type="checkbox"/> Bailer <input type="checkbox"/> Pump <input type="checkbox"/> Air Lift | | | |
| No test | | | |

10. DRILLER'S CERTIFICATION
 This well was drilled under my supervision and the report is true to the best of my knowledge.
 Name: Wayne Drilling, Inc. Contractor
 Address: P.O. Box 12370 Contractor
 Reno, Nevada 89510
 Nevada contractor's license number issued by the State Contractor's Board 0022549
 Nevada driller's license number issued by the Division of Water Resources, the on-site driller 908
 Signed: *Wayne Drilling*
 By driller performing actual drilling on site or contractor
 Date: March 3, 1999