WHITE--DIVISION OF WATER RESOURCES
CANARY--CLIENT'S COPY
PINK--WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 109967
Permit No.
Basin 087

NOTICE OF INTENT NO. 37112

CONSULANT:
1. OWNER CDM Engineers & Constructors
MAILING ADDRESS 50 W. Liberty, Suite 770
Reno, NV 89501

CLIENT:
ADDRESS AT WELL LOCATION Sparks Solvent/Fuel Site
Vista Canyon Group/Sparks Terminal property and
Union Pacific RR property

2. LOCATION SW ¼ NE ¼ Sec. 9 T 19N N/S R 20 E Washoe County
PERMIT NO. well# MW-222A (Issued by Water Resources) | 034-102-14 (Parcel No.) | Sparks, NV (Subdivision Name)

3. WORK PERFORMED
☒ New Well ☐ Replace ☐ Recondition
☐ Deepen ☒ Abandon ☐ Other

4. PROPOSED USE
☐ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☒ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☐ Rotary ☐ RVC
☐ Air ☒ Other TUBEX

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Dry, loose, brown, SILT, little sand		0	4	4
Medium dense, brown, m f SAND, some silt, water added during drilling below 4 feet @8' Little silt and gravel		4	11	7
Wet, medium dense, brown gray, c m f GRAVEL and c m f SAND		11	30	19

Date started 11-05-97, 20
Date completed 11-06-97, 20

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☐ Air Lift

	G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
NO test			

8. WELL CONSTRUCTION
Depth Drilled 30 Feet Depth Cased 30 Feet

HOLE DIAMETER (BIT SIZE)

		From	To
8 5/8 Inches		0 Feet	30 Feet
Inches		Feet	Feet
Inches		Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
4" SCH 40 PVC			0	7
12" Diameter Steel Manhole				
Locking Well Cap				

Perforations:
Type perforation Factory Sawed Slot
Size perforation 0.06
From 7 feet to 27.43 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☒ Yes ☐ No
Depth of Seal 2.8
Placement Method: ☐ Pumped ☒ Poured
Seal Type: ☒ Neat Cement ☐ Cement Grout ☐ Concrete Grout
Bentonite Seal At: 2.8-5.1
Gravel Packed: ☒ Yes ☐ No Lonestar Coarse Aquarim sand
From 5.1 feet to 30 feet

9. WATER LEVEL
Static water level 9 feet below land surface
Artesian flow G.P.M. not known P.S.I.
Water temperature °F Quality not known

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name Wayne Drilling Inc. (Contractor)
Address P.O. Box 12370 (Contractor)
Reno, NV 89510
Nevada contractor's license number issued by the State Contractor's Board 22549
Nevada driller's license number issued by the Division of Water Resources the on-site driller 908
Signed (by driller performing actual drilling on site or contractor)
Date January 13, 2003

(Rev. 12-01)

USE ADDITIONAL SHEETS IF NECESSARY

(O)-627