

PRINT OR TYPE ONLY
 DO NOT WRITE ON BACK

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO47125

CONSULTANT: OWNER Hayley & Aldrich, Inc. CLIENT: ADDRESS AT WELL LOCATION _____
 MAILING ADDRESS 6200 East 14th St. Suite A200 The Boeing Co Rocketdyne
Tucson, AZ 85711-4029 NV Field Laboratory
 2. LOCATION SW 1/4 SW 1/4 Sec. 12 T. 22N N/S R. 21 E. Washoe County
 PERMIT NO. well D-49A 077-110-22 Palomino Valley
 Issued by Water Resources Parcel No. Subdivision Name

3. WORK PERFORMED
 New Well Replace Recondition
 Deepen Abandon Other _____
 4. PROPOSED USE
 Domestic Irrigation Test
 Municipal/Industrial Monitor Stock
 5. WELL TYPE
 Cable Rotary RVC
 Air Other _____

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
CLAYEY SAND with GRAVEL Grayish red, fine to coarse sand, fine and coarse gravel, sub-angular, well graded, dry. Mixed rhyolite fragments. @36-38'		0	67	67
Increased clay.				
TUFF Tuff of Chimney Spring.		67	70	3
10-16-01 All casing removed. Borehole backfilled with neat cement. Finish at grade.				
<i>* See Plugging Log # 109989</i>				
Equipment used: Ingersoll-Rand T4W Drill Master High pressure grout mixer				
Materials used: 70 ft. tremie pipe 25 sacks Portland Cement Type II				
Location: 400 ft E of W property line 600 ft. S of N property line				
Date started <u>10-8-01</u> , 20				
Date completed <u>10-16-01</u> , 20				

8. WELL CONSTRUCTION
 Depth Drilled 70 Feet Depth Cased 70 Feet
 HOLE DIAMETER (BIT SIZE)
 From To
7 5/8 Inches 0 Feet 70 Feet
 _____ Inches _____ Feet _____ Feet
 _____ Inches _____ Feet _____ Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
5" O.D.		.188	0	70

Perforations:
 Type perforation factory sawed slot
 Size perforation 3/32 x 3
 From 50 feet to 70 feet
 From _____ feet to _____ feet
 From _____ feet to _____ feet
 From _____ feet to _____ feet

Surface Seal: Yes No Seal Type:
 Depth of Seal Abandon/Plug Neat Cement
 Placement Method: Pumped Cement Grout
 Poured Concrete Grout
 Gravel Packed: Yes No
 From _____ feet to _____ feet

9. WATER LEVEL
 Static water level 46.5 feet below land surface
 Artesian flow _____ G.P.M. N/A P.S.I.
 Water temperature cold °F Quality not known

10. DRILLER'S CERTIFICATION
 This well was drilled under my supervision and the report is true to the best of my knowledge.
 Name Wayne Drilling Inc. Contractor
 Address P.O. Box 12370 Contractor
Reno, NV 89510
 Nevada contractor's license number issued by the State Contractor's Board 0022549
 Nevada driller's license number issued by the Division of Water Resources, the on-site driller 908
 Signed Wayne Drilling Inc.
 By driller performing actual drilling on site or contractor
 Date January 8, 2003

7. WELL TEST DATA

TEST METHOD: <input type="checkbox"/> Bailer <input type="checkbox"/> Pump <input type="checkbox"/> Air Lift			
G.P.M.	Draw Down (Feet Below Static)	Time (Hours)	