

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA



Log No. 11201
 Rec. _____ 19____
 Well No. _____
 Permit No. _____
 Do not fill in.

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Owner Harry M. Lawler Driller F. R. Baxter
 Address 6752 Lauralhurst Drive Address Box 744 Lic. No. 457
Huntington Beach, Calif. 92647 Carson City, Nevada 89701
 Location of well S. E 1/4 Sec. 22, T. 11N/S, R. 23 E, in Lyon County
 or Sayre Acres Subdivision Parcel "K"
 Water will be used for Domestic Total depth of well 120 feet
 Size of drilled hole 10 5/8 inches Weight of casing per linear foot _____
 Thickness of casing 10 gage Temp. of water Cold
 Diameter and length of casing 6 inches --- 120 feet
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)
 If flowing well give flow in c.f.s. or g.p.m. and pressure _____
 If nonflowing well give depth of standing water from surface 50 feet
 If flowing well describe control works _____
(Type and size of valve, etc.)
 Date of commencement of well Nov., 10 1970 Date of completion of well Nov., 14, 1970.
 Type of well rig Rotary

LOG OF FORMATIONS

| From feet | To feet | Thickness feet | Type of material |
|-----------|---------|----------------|---------------------|
| 0 | 18 | 18 | Sand |
| 18 | 24 | 6 | Clay |
| 24 | 64 | 40 | Fine sand & shale |
| 64 | 72 | 8 | Yellow sandy clay |
| 72 | 100 | 28 | Sand & hard shale |
| 100 | 120 | 20 | Fine to course sand |

Water-bearing Formation, Casing Perforations, etc.

Chief aquifer (water-bearing formation)
 from 80 to 120 ft.

Other aquifers _____

First water at 80 feet.

Casing perforated
 from 100 to 120 ft.

Size of perforations
2/16 factory sawed

1970 NOV 17 AM 9 52

STATE ENGINEER

