MW-7

STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S REPORT

OFFICE USE ONLY
Log No. 110012
Permit No.
Basin 085

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 57547

1. OWNER Berry-Hinckley/Terribles C/O McGinley Asso.
MAILING ADDRESS 425 Maestro Dr Suite 202 Reno, NV 89511
NW

ADDRESS AT WELL LOCATION Terrible's #830
8900 La Posada Dr, Sparks, NV
Subdivision Name: N/A County: Washoe

2. LOCATION SW ¼ SW ¼ Sec 35 T 21N N/S R 20 E
PERMIT/WAIVER No. FAC ID #D-000356 | 534-09-09
Issued by Water Resources Parcel No.

Latitude 39.64263° N
Longitude 119.71313° W
UTM E N
☒ NAD 27 ☐ NAD 83/WGS 84

3. WORKED PERFORMED
☑ New Well ☐ Replace ☐ Recondition ☐ Deepen ☐ Other

4. PROPOSED USE
☐ Domestic ☐ Irrigation ☐ Test ☐ Municipal/Industrial ☑ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☐ Rotary ☐ RVC ☐ Air ☑ Other HSA

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Asphalt		.5	1	1
Fat Clay medium brown moist		1	8	7
Poorly-graded sand		8	11	3
Fat Clay with sand		11	22	11
Silt Light brown	31.4	22	40	18

39.642636°N
119.713136°W
NAD 27 (TA)

Date started: 9/23/08, 20 08
Date completed: 9/23/08, 20 08

9. WELL CONSTRUCTION
Depth Drilled 40 Feet Depth Cased 40 Feet

HOLE DIAMETER (BIT SIZE)

		From		To	
8.25	Inches	0	Feet	40	Feet
	Inches		Feet		Feet
	Inches		Feet		Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
2		Schd 40	0	25

Perforations:
Type of perforation: Machine slot
Size of perforation: 0.02
From 25 feet to 40 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Annular Seal: ☒ Yes ☐ No
☒ Neat Cement 0 to 20 ☒ Pumped ☐ Poured
☐ Cement Grout to ☐ Pumped ☐ Poured
☐ Concrete Grout to ☐ Pumped ☐ Poured
☐ ≥30% Bentonite Grout to ☐ Pumped ☐ Poured

Gravel Pack: ☑ Yes ☐ No 23 to 40 ☐ Pumped ☒ Poured
Type: 2/12 sand
Bentonite Chips: ☑ Yes ☐ No 20 to 23 ☐ Pumped ☒ Poured
Type: 3/8 inch chips

7. Water Level
Static water level: 31.4 feet below land surface
Artesian Flow: no G.P.M. N/A P.S.I.
Water Temperature: N/A °F
Quality:

8. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☐ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name PC Exploration, Inc. (Contractor)
Address 3883 Cincinnati Ave Rocklin, CA 95765 (Contractor)
Nevada contractor's license number issued by the *State Contractor's Board* 0028767
Nevada driller's license number issued by the Division of Water Resources, the *on-site driller* M-2223
Signed (By driller performing actual drilling on site or contractor)
Date 10-13-08

(Rev. 05-08)

USE ADDITIONAL SHEETS IF NECESSARY