Corrected

STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S REPORT

OFFICE USE ONLY
Log No. 110043
Permit No.
Basin 177

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 34263

1. OWNER Kenneth Johns
MAILING ADDRESS HC 60, Box 140
Wells, NV 89855

ADDRESS AT WELL LOCATION 16 Miles South West of Wells
Subdivision Name: County: Elko

2. LOCATION NE ¼ SE ¼ Sec 2 T 35N N/S R 61 E
PERMIT/WAIVER No. tract of land
Issued by Water Resources Parcel No.

Latitude Longitude
UTM E N
☐ NAD 27 ☐ NAD 83/WGS 84

3. WORKED PERFORMED
☒ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Other

4. PROPOSED USE
☒ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☐ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☒ Rotary ☐ RVC
☐ Air ☐ Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
COBBLED SUB-SOIL		0	5	5
CEMENTED GRAVEL		5	90	85
BROWN/TAN CLAY		90	100	10
CEMENTED GRAVEL		100	125	25
SAND/GRAVEL	X	125	160	35
SANDSTONE		160	190	30
CEMENTED GRAVEL		190	200	10
FRACTURED BLACK ROCK	X	200	205	5
TAN CLAY		205	240	35

40.943333 NAD27 D.D.
115.045833

Date started: 5-Nov , 20 04
Date completed: 10-Nov , 20 04

7. Water Level
Static water level: 92 feet below land surface
Artesian Flow: G.P.M. P.S.I.
Water Temperature: cold °F
Quality:

8. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☒ Air Lift

	G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
Approx	9		12.5

9. WELL CONSTRUCTION
Depth Drilled 240 Feet Depth Cased 240 Feet

HOLE DIAMETER (BIT SIZE)

		From		To	
10	Inches	0	Feet	160	Feet
6 1/4	Inches	160	Feet	240	Feet
	Inches		Feet		Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
6	12.92	188	+1	27
6	SDR-17		27	160
4 1/2	SDR-17		160	240

Perforations:
Type of perforation Mill Slot
Size of perforation 0.05
From 120 feet to 240 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Annular Seal: ☒ Yes ☐ No
☐ Neat Cement to ☐ Pumped ☐ Poured
☐ Cement Grout to ☐ Pumped ☐ Poured
☒ Concrete Grout 0 to 54 ☐ Pumped ☒ Poured
☐ ≥30% Bentonite Grout to ☐ Pumped ☐ Poured

Gravel Pack: ☒ Yes ☐ No 54 to 160 ☐ Pumped ☒ Poured
Type: PEA GRAVEL
Bentonite Chips: ☐ Yes ☐ No to ☐ Pumped ☐ Poured
Type:

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name SHAREL C. FERTIG SR., DBA FERTIG DRILLING CO.
Contractor
Address P.O. BOX 525
Contractor
ELKO, NV 89803
Nevada contractor's license number issued by the State Contractor's Board 031904
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1584
Signed
By driller performing actual drilling on site or contractor
Date 3-23-09

(Rev. 05-03)

USE ADDITIONAL SHEETS IF NECESSARY