

STATE OF NEVADA  
DIVISION OF WATER RESOURCES  
WELL DRILLER'S PLUGGING REPORT

OFFICE USE ONLY 110086  
Log No. \_\_\_\_\_  
Permit No. \_\_\_\_\_  
Basin 105

PRINT OR TYPE ONLY  
DO NOT WRITE ON BACK

Please complete this form in its entirety in  
accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 58069

1 OWNER Douglas County Utilities  
MAILING ADDRESS P.O. Box 218  
Minden, NV. 89423

ADDRESS AT WELL LOCATION Kensley Court  
Genoa, NV.

Subdivision Name: Sierra Shadows County: Douglas

2 LOCATION SW ¼ NW ¼ Sec 10 T 13N N/S R 19 E  
PERMIT/WAIVER No. 17-262-06  
Latitude 39 00.305N UTM E  NAD 27  
Longitude 119 50.592W N  NAD 83/WGS 84

Parcel No. \_\_\_\_\_

3 TYPE OF WELL  
 Domestic  Irrigation  Test  
 Municipal/Industrial  Monitor  Stock

Is this well being plugged because a replacement well was drilled? no  
If yes, what is replacement well NOI? \_\_\_\_\_

Is there an existing well log? yes  
If yes, what is NDWR well log #? 22871

4 EXISTING WELL CONSTRUCTION

Depth Drilled	175' Feet	Depth Cased	175' Feet
---------------	-----------	-------------	-----------

EXISTING CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
8"	n/a	.188	+2	175'

39.005°N NAD27 D.O.  
119.842°W

7 WELL PLUGGING PROCEDURE

Was well cleaned out to total depth?  yes  no  
If well was not cleaned out to total depth, please explain why: \_\_\_\_\_

Was the well contaminated?  yes  no  
Was the casing pulled?  yes  no  
Was the casing over drilled?  yes  no

If casing was left in place, please show where additional perforations were made:  
Additional Perforations: \_\_\_\_\_

Existing Perforations:

Type of perforation	Size of perforation	From	feet to	feet
mill slot	3x3/32	85'	feet to	170'

Mills Knife

Type of perforator used:	From	feet to	feet	Number of perfs per linear foot
Mills Knife	85'	feet to	5'	6

5 WATER LEVEL

Static water level 44.6' feet below land surface  
Artesian flow \_\_\_\_\_ G.P.M. P.S.I.  
Water temperature \_\_\_\_\_ ° F Quality \_\_\_\_\_

8 WELL PLUGGING MATERIALS

From	feet to	feet	Material Used	<input checked="" type="checkbox"/> Pumped	<input type="checkbox"/> Poured
174'	feet to	5'	neat cement	<input checked="" type="checkbox"/>	<input type="checkbox"/>
From	feet to	feet		<input type="checkbox"/>	<input type="checkbox"/>
From	feet to	feet		<input type="checkbox"/>	<input type="checkbox"/>
From	feet to	feet		<input type="checkbox"/>	<input type="checkbox"/>
From	feet to	feet		<input type="checkbox"/>	<input type="checkbox"/>
From	feet to	feet		<input type="checkbox"/>	<input type="checkbox"/>

6 Additional Notes or Comments

Removed 147' of 3" drop pipe with 7 1/2 hp submersible pump. Measured static water level @ 44.6' and depth of well @ 169'. Installed 2" pipe & blew debris to 174' where we hit hard bottom. We set bottom of tremmie pipe @ 168'. The next day we pumped in approx. 3-4 yards of neat cement from bottom of well to surface. The casing was then cut off 5' below grade. Casing was also perforated from 85' to 5' with Mills Knife

Neat Cement Fluid Weight 14.5 lbs/gal  
Bentonite Grout % bentonite \_\_\_\_\_  
Date Started 5/26/2009  
Date Completed 5/27/2009

9 DRILLER'S CERTIFICATION

This well was plugged and abandoned under my supervision and this report is true to the best of my knowledge.

Name Carson Pump LLC Contractor  
Address P.O. Box 20159 Contractor  
Carson City, NV. 89721

Nevada contractor's license number issued by the State Contractor's Board 39920A  
Nevada driller's license number issued by the Division of Water Resources the on-site driller R&P-LTD2265

Signed Joe Carter  
Date 6/5/2009