



LOG FOR BORING NO. <u>1, 2 (3)</u>		JOB NAME: <u>L.V. PAVING</u>			
DATE STARTED <u>11-19-09</u>	DATE COMPLETED	LOGGED BY <u>Ed</u>	DRILLED BY <u>Ed</u>	TYPE OF DRILL RIG	JOB NO. <u>5970</u>
DEPTH OF HOLE <u>40'</u>	DIAMETER OF HOLE <u>24"</u>	CASING <u>8"</u>	PERFORATIONS <u>20'</u>	SAMPLING METHOD	ELEVATION
LOCATION <u>see back</u>				DRILLERS NOTES:	

man hole #116 Sta. 444+5933

DEPTH	SAMPLES	GRAPHIC	DESCRIPTION
			<u>Packed Red SILT</u>
			<u>soft SILTY SAND</u>
10'		<u>moist</u>	<u>Gray</u>
			<u>silty clay</u>
20'			
			<u>hard clay</u>
30'			<u>soft silty clay</u>
40'			
50'			
60'			
70'			
80'			
90'			
100'			

Red silt is a very fine powder which settles out real tight at the bottom of the casing. Hydro mud helps, and the well must be cleaned out quickly before it settles.

DCNR/DWR  
RECEIVED

FEB 05 2010

LAS VEGAS OFFICE

NOV 30 2009