FINALIZED NA

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 110499
Permit No.
Basin 108

NOTICE OF INTENT NO. NA

1. OWNER Berry-Hinkley Industries
MAILING ADDRESS 1180 W. Fourth Street, Reno, NV 89503

ADDRESS AT WELL LOCATION DPE-4
#1 Hwy 95-A & Goldfield, Yerington, NV 89447
Subdivision Name: County: Lyon

2. LOCATION NE ¼ NE ¼ Sec 16 T 13 N/S R 25 E
PERMIT/WAIVER No. NA
Issued by Water Resources Parcel No.

Latitude 38.99461035556
Longitude -119.18159889444
UTM E N
[X] NAD 27 [ ] NAD 83/WGS 84

3. WORKED PERFORMED
[X] New Well [ ] Replace [ ] Recondition
[ ] Deepen [ ] Other

4. PROPOSED USE
[ ] Domestic [ ] Irrigation [ ] Test
[ ] Municipal/Industrial [X] Monitor [ ] Stock

5. WELL TYPE
[ ] Cable [ ] Rotary [ ] RVC
[ ] Air [X] Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Asphalt and Fill		0	1	1
Silty/Clayey Sand		1	9	8
Well Graded Sand		9	10	1
Silty/Clayey Sand		10	13	3
Well Graded Sand		13	15	2

38.994, 610°N NAD27 D.D.
119.181, 599°W

Date started: 7-Jul , 20 06
Date completed: 7-Jul , 20 06

9. WELL CONSTRUCTION
Depth Drilled 15 Feet Depth Cased 15 Feet

HOLE DIAMETER (BIT SIZE)

		From		To	
10	Inches	0	Feet	15	Feet
	Inches		Feet		Feet
	Inches		Feet		Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
4		sch.40	1	15

Perforations:
Type of perforation Slotted
Size of perforation 0.01
From 8 feet to 13 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Annular Seal: [X] Yes [ ] No
[X] Neat Cement 1 to 7 [X] Pumped [ ] Poured
[ ] Cement Grout to [ ] Pumped [ ] Poured
[X] Concrete Grout 0 to 1 [ ] Pumped [X] Poured
[ ] ≥30% Bentonite Grout to [ ] Pumped [ ] Poured

Gravel Pack: [X] Yes [ ] No 7 to 13 [ ] Pumped [X] Poured
Type: 2/16 silica sand
Bentonite Chips: [X] Yes [ ] No 6 to 7 [ ] Pumped [X] Poured
Type: 3/8 chips

7. Water Level
Static water level: 4 feet below land surface
Artesian Flow: no G.P.M. n/a P.S.I.
Water Temperature: n/a °F
Quality:

8. WELL TEST DATA
TEST METHOD: [ ] Bailer [ ] Pump [ ] Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name PC Exploration Inc. (Contractor)
Address 2905 Lesvos Court, Lincoln, CA 95648 (Contractor)
0028767
Nevada contractor's license number issued by the *State Contractor's Board* M 2223
Nevada driller's license number issued by the Division of Water Resources, the *on-site driller* Sonne Fleming
Signed (By driller performing actual drilling on site or contractor)
Date 1/27/2010

(Rev. 05-06)

USE ADDITIONAL SHEETS IF NECESSARY