

FINALIZED MH

STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S REPORT

OFFICE USE ONLY
Log No. 110706
Permit No.
Basin 674

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 64377

1. OWNER Pilot Travel Centers, LLC
MAILING ADDRESS 5508 Lewis Rd
Knoxville, TN 37909

ADDRESS AT WELL LOCATION 5625 West I-80
Winnemucca, NV 89445
Subdivision Name:
County: Humboldt

2. LOCATION SE 1/4 35 1/2 Sec 43 T 35 R 37 E
PERMIT/WAIVER No. Fact 5-000212 013-081-04
Issued by Water Resources Parcel No.

Latitude N 40.93105° UTM E NAD 27
Longitude W 117.80513° N NAD 83/WGS 84

3. WORKED PERFORMED
New Well Replace Recondition
Deepen Other

4. PROPOSED USE
Domestic Irrigation Test
Municipal/Industrial Monitor Stock

5. WELL TYPE
Cable Rotary RVC
Air Other AUGER

LITHOLOGIC LOG table with columns: Material, Water Strata, From, To, Thickness. Includes handwritten entries: silt gravel, sand gravel, sand, VE-14, Please note: No I # 64377 showed this well as a replacement well # MW-1. Could not overdrill MW-1 cause of fiber optic line that was installed 10' away from well. So we moved over 3' and drilled new well and labeled it VE 14.

9. WELL CONSTRUCTION table with columns: Depth Drilled, Feet, Depth Cased, Feet. Includes HOLE DIAMETER (BIT SIZE) table with columns: From, To, Inches, Feet.

CASING SCHEDULE table with columns: Size O.D. (Inches), Weight/Ft. (Pounds), Wall Thickness (Inches), From (Feet), To (Feet). Includes handwritten entry: 4 SCH. 40 0 10.

Perforations:
Type of perforation Factory slot
Size of perforation .020
From 10 feet to 25 feet

Annular Seal: Yes No
Neat Cement to Pumped Poured
Cement Grout 0 to 6 Pumped Poured
Concrete Grout to Pumped Poured
230% Bentonite Grout to Pumped Poured

Gravel Pack: Yes No 8 to 25 Pumped Poured
Type: 10/20 / 5/11 ca. sand
Bentonite Chips: Yes No 6 to 8 Pumped Poured
Type: 3/8 Bentonite chips

Date started: April 12th 20 10
Date completed: April 12th 20 10

7. Water Level
Static water level: 14 feet below land surface
Artesian Flow: No G.P.M. P.S.I.
Water Temperature: 28.5 °F
Quality:

8. WELL TEST DATA table with columns: TEST METHOD (Bailer, Pump, Air Lift), G.P.M., Draw Down (Feet Below Static), Time (Hours). Includes handwritten notes: STATE ENGINEERS OFFICE, 2010 MAY - 5 AM 11:04, RECEIVED.

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name: HAZ-Tech Drilling, Inc. Contractor
Address: P.O. Box 940 Contractor
Meridian Id. 83680
Nevada contractor's license number issued by the State Contractor's Board: 0038018
Nevada driller's license number issued by the Division of Water Resources, the on-site driller: M-1803T-1
Signed: [Signature] By driller performing actual drilling on site or contractor
Date: 4/25/10

USE ADDITIONAL SHEETS IF NECESSARY 40.931147N
117.805215W
76767