STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S REPORT

OFFICE USE ONLY
Log No. 110772
Permit No.
Basin

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 34354

1. OWNER Clark County (PK & COMM)
MAILING ADDRESS 500 S. Grand Central Pkwy
Las Vegas, NV

ADDRESS AT WELL LOCATION 200 E Virginia
Subdivision Name: County: Clark

2. LOCATION NE ¼ SE ¼ Sec 13 T 16S N/S R 67 E
PERMIT/WAIVER No. DW-1299 (Issued by Water Resources) 7013701017 Parcel No.

Latitude 36 32'25.79
Longitude 114 26'25.98
UTM E N
☐ NAD 27 ☒ NAD 83/WGS 84

3. WORKED PERFORMED
☒ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Other

4. PROPOSED USE
☐ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☐ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☐ Rotary ☐ RVC
☐ Air ☒ Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
See Attached Well #61				
Log # 6				

Date started: 8-Dec, 20 09
Date completed: 8-Dec, 20 09

FEB 05 2010

9. WELL CONSTRUCTION
Depth Drilled 40 Feet Depth Cased 40 Feet

HOLE DIAMETER (BIT SIZE)

		From		To	
24	Inches	0	Feet	40	Feet
	Inches		Feet		Feet
	Inches		Feet		Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
8	6	3/8	0	40

Perforations:
Type of perforation machine slot
Size of perforation 0.032
From 20 feet to 40 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Annular Seal: ☒ Yes ☐ No
☐ Neat Cement to ☐ Pumped ☐ Poured
☐ Cement Grout to ☐ Pumped ☐ Poured
☐ Concrete Grout to ☐ Pumped ☐ Poured
☒ ≥30% Bentonite Grout 10 to 12 ☐ Pumped ☒ Poured
Gravel Pack: ☒ Yes ☐ No 12 to 40 ☐ Pumped ☒ Poured
Type: 3/8 Pea Gravel
Bentonite Chips: ☒ Yes ☐ No 10 to 12 ☐ Pumped ☒ Poured
Type: 3/8's

7. Water Level
Static water level: 7 feet below land surface
Artesian Flow: G.P.M. P.S.I.
Water Temperature: °F
Quality:

8. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☐ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name Viking Drillers Inc (Contractor)
Address 801 Northport Dr. (Contractor)
West Sacramento, CA
Nevada contractor's license number issued by the State Contractor's Board 0034680
Nevada driller's license number issued by the Division of Water Resources, the on-site driller DEW-2361
Signed (By driller performing actual drilling on site or contractor)
Date 1/29/2010

(Rev. 05-06)

USE ADDITIONAL SHEETS IF NECESSARY

THIS BORING LOG IS FOR VIKING'S RNAL PURPOSES ONLY. IT DOES NOT REPRESENT ORMATION PROVIDED BY A SOILS ENGINEER.

LOG FOR BORING NO. 5,6		JOB NAME: LV. Paving			
DATE STARTED 12-8-09	DATE COMPLETED	LOGGED BY Ed	DRILLED BY Ed	TYPE OF DRILL RIG # 31	JOB NO. 5970
DEPTH OF HOLE 40'	DIAMETER OF HOLE 24"	CASING 8"	PERFORATIONS 20'	SAMPLING METHOD	ELEVATION
LOCATION 415+50 TO 415+00 See back				DRILLERS NOTES:	

DEPTH	SAMPLES	GRAPHIC	DESCRIPTION
			Red clay
			silty sand
			Rock & silt
10'			silty sand
20'			tight sand
			soft silty clay
30'			hard clay
			silty sand
40'			
50'			
60'			
70'			
80'			
90'			
100'			

FEB 05 2010

DEC 14 2009